

Manley Massive Passive

Šifra: 23124

Kategorija proizvoda: Ekvilajzeri

Proizvođač: Manley



Cena: 719.760,00 rsd

Specifications 2020 Version Driven by Manley Power®

Inputs: Balanced XLR & 1/4" (accepts unbalanced)

Outputs: Balanced XLR (accepts unbalanced) & Unbalanced 1/4"

Level +4 dBu nominal

Bypass Switch bypasses EQ & tube circuits: 1/4" Jacks (not hardwire)

Bypass Switch bypasses EQ, tube circuits & Input Buffer: XLR Jacks (Hardwire Bypass)

Gain Trim: -6dB - 0dB - +4dB

44 Frequencies (roughly 1/4 octave spacing)

Frequency Range: 22 Hz to 27 kHz

EQ Boost/Cut Range: Maximum 20 dB boost or cut

Nominal Q range: 1.5 to 3 (uniquely active in shelf modes)

Maximum Input Level: +21dBu

Maximum Output Level (1kHz sine, 1% THD+N, BW 22Hz-22kHz, Load 100kOhms): +35dBu

Frequency Response (@ +4dBu, Load 100kOhms): -0.1 dB @ 10Hz, -1 dB @ 60 kHz

Total Harmonic Distortion (THD+N) (1kHz sine @ +4dBu, BW 22Hz-22kHz): 0.006%

Output Headroom (Reference to +4dBu): 31dB

Dynamic Range (Reference to Maximum Output): 123 dB

Noise Floor Typical (Unity Gain): -88 dBu (A-Weighted)

Signal to Noise Ratio (Reference to +4 dBu, BW 22Hz-22kHz): 92dB

Input Impedance: 20kOhm

Output Impedance: 150 Ohm

Tube Complement: 2 x 5751, 4 x 6922

Auto-mute warmup delay = 20 seconds

Power Consumption (120/240VAC): 44 watts

Mains Voltage & Frequency (VAC/Hz): Internal Universal Power Supply 90-254 VAC / 50-60Hz

Size (3U): L 19" x W 10" x H 5.25"

Unit Weight: 15.5 Lbs.

Shipping Box: L 23" x W 15" x H 10"

Shipping Weight: 26 Lbs.

Features

- All-Passive tone sculpting circuitry
- Unique Shelf curves use the "bandwidth" control
- Overlapping and Interleaved Frequency choices
- Every band switchable to shelf or bell
- Vacuum tube make-up gain and line drivers
- Parallel symmetrical topology
- Premium components throughout
- Passive HP and LP Filters plus gain trims

- Units built after 2016 or 2017 MK2 revision have Hardwire Bypass.