

MARTIN WISMAN ECX 104

Šifra: 322
 Kategorija prozivoda: Skretnice
 Proizvođač: Martin Wisman

Cena: 10.680,00 rsd

INPUTS

Connectors	XLR
Type	Electronically servo-balanced, HF filtered
Impedance	>50 Khom @ balanced, >25 Khom @ unbalanced
Max input level	+22dB
CMRR	>40dB (typical), >55dB @ 1KHz

OUTPUTS

Connectors	XLR
Type	Electronically servo-balanced
Impedance	200 Khom @ balanced, 100 Khom @ unbalanced
Max output level	+20dB @ balanced, +26dB @ unbalanced

PERFORMANCE

Brandwith	20Hz to 20Khz	+/-0.5dB
Frequency response	5Hz to 60Khz	+/-3dB
Signal noise ratio	ref: +4dB, 20Hz to 20Khz, unweighted	
Mode	stereo	mono
Low output	>93dB	>93dB
Mid output		95dB
High output	>91dB	>91dB
Crosstalk	High to Low	<93dB
	High to mid	<94dB
	Mid to low	<95dB

CROSSOVER

Filter type	Likwitz-Riley, 24db/octave, state-variable	
Stereo mode frequencies	x1	x10
Low/High	45 to 960 Hz	450Hz to9.6Khz
Mono mode frequencies	x1	x10
Low/mid	45 to 960 Hz	450Hz to 9.6Khz
Mid/High	45 to 960 Hz	450Hz to 9.6Khz

POWER SUPPLY

Mains voltage	AC110V/220V;120V;220V;230V Refer to the nameplate on the rear panel
power consumption	<15W
Fuse	T500mA 250V

Mains connection

Standard IEC receptable

PHYSICAL/WEIGHT

Dimensions

apprpx 44.5mm x 482.6mm x 217mm

Weight

approx 3Kg