

ESI uniK 05+

Šifra: 7713
Kategorija proizvoda: Studijski Monitori
Proizvođač: ESI

Cena: 15.480,00 rsd

What makes uniK 05+ unique?

The uniK 05+ studio monitor offers true full range quality with extended low end in a small case and an entirely new signal processing and amplifier unit with a perfect order low-z and low noise design. Mos-Fet Bi-amplification ensures a high slew-rate

and fast setting, featuring true analog vintage sound processing with LC-like gyrator technology for a stressless and silky sound.

A completely new feature is the unique one knob sound character adjustment from smooth to bright, allowing you to change parameters for every room and preference. The additional high resolution High and Low switches add additional control. And of course the uniK 05+ studio monitor features a real precision gain attenuator, instead of a simple volume control.


The new design of the crossover ensures an excellent phase response and safe power limitation, driving the woofer and tweeter in phase for optimal step response. The tweeter features a newly upgraded magnetostatic design with extremely low moving mass for extended frequency and fast transient response and high sound resolution. The matching woofer consists of a kevlar composite cone with high stiffness ensuring better piston motion and excellent low-end sound reproduction.

Another new feature is the flexible rubber feet with discrete height adjustment. They are not only helpful to reduce unwanted vibrations, but also allow you to tilt the speaker towards the precise listening point - a great feature for typical near field applications.


Other new special features that are not standard in this class are standby to save power consumption (can be disabled) and a ground lift switch.

And with it's copper color woofer cone and the high quality matte cabinet finish, it looks quite *uniK*, too!


ROOM ADJUSTMENTS



SIDE - TILT UP



SIDE - TILT DOWN



Features

Biamp 2-Way Powered Speaker System
HF Driver: extremely low mass magnetostatic tweeter Ø49 x 26 mm
Output Power: 80W (HF: 40W, LF: 40W), 110W AC consumption power
Input Impedance: 27.2kOhm (balanced) / 13.6kOhm (unbalanced)

SPL: 101dB, Peak 104dB

Gain Control: -14 .. 0dB .. +14
Rear Bass-Reflex ventilation, optimized for near field application

Standby function, can be turned on and off
Feet: 4 pieces rubberized, adjustable height separately
Dimensions (W x H x D): 190 x 265 x 210mm

Active Studio Monitor Speaker
LF Driver: 5" kevlar curved cone (magnetic shielding type)

Frequency Response: 49Hz - 25kHz

Crossover Point: 3.2kHz
Input Connectors: XLR / TRS 1/4" combo connector, balanced / unbalanced
Room Adjustments Control: Character: -6 .. 0dB .. +6; Low: -5 .. 0dB .. +5; High: -5 .. 0dB .. +5

Ground lift switch
Indicator: multi color LED on front panel, power on orange, standby red

Working Voltage: AC100-240V 50/60Hz
Weight: 4.4 kg

