

## EVE AUDIO SC204 - Studijski monitor

Šifra: 10346  
 Kategorija proizvoda: Aktivni Studijski Monitori  
 Proizvođač: EVE Audio

**Cena: 37.920,00 rsd**

SC204 will surprise you with a very powerful, tight and precise low end.

Our AMT tweeter is our own proprietary technology that follows the rule of no off-the-shelf components in order to achieve superior results. The preciseness and detail of the high frequency range of EVE monitors, coupled with the general tightness of the bass and mid-range, make the SC204 a superb speaker that is easily used on the road (due to its reduced size) or as a second pair of speakers for your main setup.

### DSP

With every EVE Audio speaker, you also get high resolution DSP electronics. One push knob operation and you will have access to accurate volume control and several different filter settings that will help you tailor your monitors to the way you work.

And if you always avoid digital processing, we've got you covered. The DSP engine is supported with a high quality A/D converter (24bit/192kHz) from Burr-Brown, which delivers a pristine signal to the DSP section. And since the PWM amplifiers are directly connected to the DSP, no additional conversion is necessary.

### Bass Port Design

It's all in the geometry. One of the downside effects of port compression is bass distortion. As you turn up the volume, the efficiency of the port reduces and distortion will increase.

We opted for a large rear rectangular port with no hard edges for our bass port designs. That's one of the reasons EVE monitors have a high efficiency on the lower frequencies.

The results? High sound pressures with tight and punchy bass frequencies that don't cause port distortion. Crank up the volume, and EVE will deliver a round bass. With no holes to look at every time you glance at your speakers.

### Measurements

Freq. response  
 Polar pattern  
 Distortion  
 Product SC204  
 Description 2-way System  
 Dimensions (WxHxD) [mm] 145 x 230 x 195  
 Dimensions (WxHxD) ["] 5.71 x 9.06 x 7.68  
 Free-field frequency range (-3dB) 64Hz - 21kHz  
 Tweeter AMT RS1  
 Mid-Woofer 100mm/4"  
 Cross-over frequency 3000Hz  
 Maximum SPL @ 1m 96dB  
 Number of amplifiers 2  
 Output power (woofer) 50W

### EVE AUDIO SC204 - Studijski monitor

**Tech  
Talk**

The SC204 uses a 4" SilverCone woofer with honeycomb structured diaphragm, driven by a sophisticated low distortion copper cap magnet system with a 1" voice coil responsible for creating a greater linear excursion. This produces a bigger dynamic than one would assume in a monitor of such small proportions. As a result, in addition to the unsurpassed audio transparency of our proprietary AMT tweeter and PWM amplifier combination, this

Output power (tweeter) 50W

Protection limiter

Settings

Volume -inf. - +6dB

High-shelf filter (-5dB - +3dB) > 3kHz

Desk filter boost (0dB - +3dB) 80Hz

Desk filter cut (-5dB - 0dB) 200Hz

Low-shelf filter (-5dB - +3dB) < 300Hz

LED brightness setting

Level-lock dip switch

Filter-lock dip switch

Connectors

XLR in (impedance) (10k)

RCA in (impedance) (10k)

Power consumption

Standby < 1W

Full output 70VA

Misc.

Backmounting thread inserts

Mic stand thread inserts

Weight kg/lb. 3.8 / 8.4