

## FBT VERTUS CLA 118SA - Aktivni vufer

Šifra: 12035  
 Kategorija proizvoda: Aktivni Subwooferi  
 Proizvođač: FBT



**Cena: 179.880,00 rsd**

Compared to a traditional two-way speaker, the sound is distributed in a much more uniform manner into the listening area, regardless of whether the application is indoors, outdoors or acoustically difficult in terms of reverberation. The cylindrical wave front of the CLA projects sound forwards in a very precise and coherent fashion without the reverberant performance that is typical of conventional speakers which can excite environmental reflections, directing acoustic energy where it is not needed, especially towards the ceiling and floor. Even acoustic feedback such as that generated by microphones is rejected to a far greater extent than a conventional enclosure.

Finally, the columns narrow dimensions allow the discreet, unobtrusive integration of the column into any environment.

### **The qualities of the system CLA can be summarized as:**

High-end sound quality with a **frequency response of 33Hz to 20kHz**, designed specifically for live  
 Improved dispersion within a set listening area plus extended projection

High power performance and dynamic range thanks to the tri-amplification system

Portability and modularity – elements can be rapidly daisy-chained via a quick release system, extending both the vertical directivity and sound pressure level

Design and elegance for easy integration even in the most demanding installations – the compact dimensions ensure listeners will focus on the sound and not the speaker!

Wide horizontal dispersion

### **Processed Active Subwoofer**

**1200W - 138 dB SPL**

### **Active subwoofer in bass-reflex design**

**460mm (18") B&C high excursion woofer with 75mm (3") voice coil**

Frequency response from 33Hz to 100Hz

**1200W RMS Class D power amplifier** with switching mode power supply

Processor **DSP with 8 presets**, cardioid configuration, delay

Control Panel with XLR input and link, volume, presets, delay, phase 0 ° -180 °, ground-lift

**Neutrik powerCON** power IN and LINK connectors

15mm (5/8") birch plywood with scratch-resistant coating Stackable

M20 (20mm) top mount speaker stand socket, two diecast aluminium carrying handles with rubber inserts

Optional 4 swivel-mount casters 80mm (3.15") on request

Suitable for low frequency extension and reinforcement of the **CLA406A** array, especially for live performance

Configuration:	1 reflex way
Built-in amplifier LF/HF:	1200 W RMS

Built-in amplifier peak LF/HF:	2400 W
Frequency response:	33Hz - 120Hz -6dB
Low Frequency woofer:	1x18 -3 coil inch
Maximum SPL cont/peak:	134/138 half-space dB
Dispersion:	omnidirectional HxV
Input impedance:	22 Kohm
Crossover Frequency:	preset dependant KHz
AC Power requirements:	640 VA
Input connector:	XLR with loop
Power cord:	5 / 16.4 m/ft
Net Dimension (WxHxD):	550x550x660 / 21.65x21.65x25.98 mm/inch
Net Weight:	40/88.18 kg/lb
Transport Dimension (WxHxD):	700x700x800 / 27.55x27.55x31.49 mm/inch
Transport Weight:	50/110.23 Kg/lb