

# FBT VERTUS CLA 118SA - Aktivni vufer

Šifra: 12035  
Kategorija proizvoda: Aktivni Subwooferi  
Proizvođač: FBT

Cena: 179.880,00 rsd

Compared to a traditional two-way speaker, the sound is distributed in a much more uniform manner into the listening area, regardless of whether the application is indoors, outdoors or acoustically difficult in terms of reverberation. The cylindrical wave front of the CLA projects sound forwards in a very precise and coherent fashion without the reverberant performance that is typical of conventional speakers which can excite environmental reflections, directing acoustic energy where it is not needed, especially towards the ceiling and floor. Even acoustic feedback such as that generated by microphones is rejected to a far greater extent than a conventional enclosure. Finally, the columns narrow dimensions allow the discreet, unobtrusive integration of the column into any environment.

## The qualities of the system CLA can be summarized as:

- High-end sound quality with a **frequency response of 33Hz to 20kHz**, designed specifically for live
- Improved dispersion within a set listening area plus extended projection
  - Portability and modularity – elements can be rapidly daisy-chained via a quick release system, extending both the vertical directivity and sound pressure level
  - Wide horizontal dispersion
- High
  - the tr
  - Design
  - most
  - ensur
  - speak

## Processed Active Subwoofer 1200W - 138 dB SPL

- Active subwoofer in bass-reflex design
- 460mm (18") B&C high excursion woofer with 75mm (3") voice coil
  - 1200W RMS Class D power amplifier with switching mode power supply
  - Control Panel with XLR input and link, volume, presets, delay, phase 0 ° -180 °, ground-lift
  - 15mm (5/8") birch plywood with scratch-resistant coating Stackable
  - Optional 4 swivel-mount casters 80mm (3.15") on request
- Frequ
  - Proce
  - delay
  - Neut
  - M20 (
  - dieca
  - Suita
  - of the

Configuration:	1 reflex way
Built-in amplifier LF/HF:	1200 W RMS
Built-in amplifier peak LF/HF:	2400 W
Frequency response:	33Hz - 120Hz -6dB
Low Frequency woofer:	1x18 -3 coil inch
Maximum SPL cont/peak:	134/138 half-space dB
Dispersion:	omnidirectional HxV
Input impedance:	22 Kohm

Crossover Frequency:	preset dependant KHz
AC Power requirements:	640 VA
Input connector:	XLR with loop
Power cord:	5 / 16.4 m/ft
Net Dimension (WxHxD):	550x550x660 / 21.65x21.65x25.98 mm/inch
Net Weight:	40/88.18 kg/lb
Transport Dimension (WxHxD):	700x700x800 / 27.55x27.55x31.49 mm/inch
Transport Weight:	50/110.23 Kg/lb