

FBT VERTUS CLA 406A B-Stock

Šifra: 12034
Kategorija proizvoda: Aktivne Zvučne Kutije
Proizvođač: FBT

Cena: 191.880,00 rsd

environmental reflections, directing acoustic energy where it is not needed, especially towards the ceiling and floor. Even acoustic feedback such as that generated by microphones is rejected to a far greater extent than a conventional enclosure.

Finally, the columns narrow dimensions allow the discreet, unobtrusive integration of the column into any environment.

The qualities of the system CLA can be summarized as:

High-end sound quality with a **frequency response of 33Hz to 20kHz**, designed specifically for live

High power performance and dynamic range thanks to the tri-amplification system

Design and elegance for easy integration even in the most demanding installations - the compact dimensions ensure listeners will focus on the sound and not the speaker!

Improved dispersion within a set listening area plus extended projection

Portability and modularity - elements can be rapidly daisy-chained via a quick release system, extending both the vertical directivity and sound pressure level

Wide horizontal dispersion

VERTUS CLA 406A

600W + 300W

133 dB SPL

Active Column Line Array

2-way bi-amplified line array column system

B&C HF neodymium driver with 36mm (1.4") exit and 64mm (2.5") voice coil

Frequency response from 65Hz to 20KHz

Processor **DSP** with **8 EQ presets**

Neutrik powerCON power IN and LINK connectors
12 attachment points above and below for the optional hardware that allows the installation of hanging or pair two CLA406A with angle of 0 ° - 10 ° - 20 ° in the vertical plane

35mm (1.3/8") top hat for stand mount facility

4 x 165mm (6.5") custom woofer voice coil 38mm (1.5")

Waveguide FBT large format with dispersion 100 ° H x 25 ° V

Amplifiers **Class D 600Wrms for LF and HF 300Wrms** with switching power supply

Control Panel with XLR input and link, volume, presets, filter-HP, ground-lift

12mm (1/2") birch plywood with scratch-resistant coating.

Top side tilted 10 ° for the inclination of two columns without damaging gap between the waveguides for a wavefront extremely consistent over the 18kHz

It is ideal for live applications, assisted by sub **CLA 118SA**, which for fixed installations

Built-in amplifier LF/HF:	600/300 W RMS
Built-in amplifier peak LF/HF:	1200/600 W
Frequency response:	65Hz - 20KHz -6dB
Low frequency woofer:	4x6.5 - 1.5 coil inch
High frequency driver:	1x1.4 - 2.5 coil - neodymium inch

Maximum SPL cont/peak:	133 dB
Dispersion:	100°x25° H x V
Input impedance:	22 Kohm
Crossover frequency:	1.2 KHz
Ac power requirements:	640 VA
Input connector:	XLR with loop
Power cord:	5 / 16.4 mm/inch
Net Dimension (WxHxD):	190x1235x290 / 7.48x44.68x11.41 mm/inch
Net weight:	27 / 59.52 kg/lb
Transport Dimension (WxHxD):	290x1235x390 / 11.41x48.62x15.35 mm/inch
Transport weight:	32 / 70.54 kg/lb