

FBT EvoMaxX 6

Šifra: 7565
Kategorija proizvoda: Pasivne Zvučne Kutije
Proizvođač: FBT

Cena: **76.680,00** rsd

EvoMaxX 6 400W /8ohm 130dB SPL Passive Sound Reinforcement Speaker

- Passive version, recommended amplifier 400W RMS @ 8 ohms
- Built-in passive crossover with soft-trip protection for the LF woofer and HF driver
- Speakon NL-4 IN and LINK OUT connectors

FBT EvoMaxX 6 400W 15" Passive Speaker, FBT EvoMaxX 6, 400W / 8 ohms 126 / 130dB SPL Passive Sound Reinforcement Speaker. Evolving from the FBT MaxX Series of loudspeakers, the FBT EvoMaxX 6 passive speaker features a new woofer. The Evo MaxX 6 also has been developed by one very important goal - offering the customer more value for money.

The EvoMaxX6's lightweight yet sturdy polypropylene cabinet features a monitor taper designed to ensure that it performs with excellence no matter whether they are used at front of house for a main sound system, as stage floor monitors or within permanent installations. Additional options are also available for extending low frequency response in the shape of the Subline 15Sa and 18Sa, all of which boast birch plywood enclosures with 15" band-pass and 18" reflex designs respectively. The EvoMaxX series consists of four powered and three passive models.

Features

Passive version, recommended amplifier 400W RMS @ 8 ohms	Built-in passive crossover with soft-trip protection for the LF woofer and HF driver	Speakon NL-4 IN and LINK OUT connectors
--	--	---

Specification

Configuration: 2 way	Recommended Amplifier: 400W RMS Nominal Impedance: 8 Ohm Low Frequency Woofer: 1x15" - 2.5" coil - neodymium Sensitivity (@1W/1m): 99dB Dispersion H x V: 90° x 60° Recommended HP Filter: 40Hz - 24dboct Net Dimensions (WxHxD): 482 x 757 x 399mm, (19 x 29.8 x 15.7") Transport Dimensions (WxHxD): 595 x 878 x 515mm (23.4 x 34.6 x 20.3")	Short Throw Frequency Response: 60Hz - 18kHz High Frequency Driver: 1" dome Maximum Power: 400W Crossover: 2nd order, 24dB/oct Inputs: 2x Speakon NL4 Net Weight: 12.5kg Transport Weight: 13.5kg
----------------------	---	--