

## FBT EvoMaxX 6

Šifra: 7565  
Kategorija proizvoda: Pasivne Zvučne Kutije  
Proizvođač: FBT

**Cena: 76.680,00 rsd**

FBT EvoMaxX 6  
Image not found or type unknown

### EvoMaxX 6 400W /8ohm 130dB SPL Passive Sound Reinforcement Speaker

- Passive version, recommended amplifier 400W RMS @ 8 ohms
- Built-in passive crossover with soft-trip protection for the LF woofer and HF driver
- Speakon NL-4 IN and LINK OUT connectors

**FBT EvoMaxX 6 400W 15" Passive Speaker**, FBT EvoMaxX 6, 400W / 8 ohms 126 / 130dB SPL Passive Sound Reinforcement Speaker. Evolving from the FBT MaxX Series of loudspeakers, the FBT EvoMaxX 6 passive speaker features a new woofer. The Evo MaxX 6 also has been developed by one very important goal - offering the customer more value for money.

The EvoMaxX6's lightweight yet sturdy polypropylene cabinet features a monitor taper designed to ensure that it performs with excellence no matter whether they are used at front of house for a main sound system, as stage floor monitors or within permanent installations. Additional options are also available for extending low frequency response in the shape of the Subline 15Sa and 18Sa, all of which boast birch plywood enclosures with 15" band-pass and 18" reflex designs respectively. The EvoMaxX series consists of four powered and three passive models.

### Features

Passive version, recommended amplifier 400W RMS @ 8 ohms

Built-in passive crossover with soft-trip protection for the LF woofer and HF driver

Speakon NL-4 IN and LINK OUT connectors

### Specification

Configuration: 2 way

Short Term Power: 800w IEC 268-5

Frequency Response: 48Hz - 18kHz @-6dB

High Frequency Driver: 1 x 1" - 1.7" coil

Maximum SPL Cont/Peak (Bi-Amp): 126 / 130 dB

Crossover Frequency: 1.3 kHz

Input Connectors: 2 x Speakon NL4 in & thru

Net Weight: 21 kg (46.9lb)

Transport Weight: 25 kg (55.7lb)

Recommended Amplifier: 400W RMS

Nominal Impedance: 8 Ohm

Low Frequency Woofer: 1x15" - 2.5" coil - neodymium

Sensitivity (@1W/1m): 99dB

Dispersion H x V: 90° x 60°

Recommended HP Filter: 40Hz - 24dboct

Net Dimensions (WxHxD): 482 x 757 x 399mm, (19 x 29.8 x 15.7")

Transport Dimensions (WxHxD): 595 x 878 x 515mm (23.4 x 34.6 x 20.3")