

FBT Maxx 2

Šifra: 3710
Kategorija proizvoda: Pasivne Zvučne Kutije
Proizvođač: FBT

Cena: **33.480,00** rsd

Sound Reinforcement Monitor 200W

- Extremely light and sturdy enclosure made of polypropylene with gas injection moulding.
- Custom horn, handled and stand adapter built into the structure
- It can be used in all audio-professional amplification systems
- Profile for use as a stage monitor
- Four anchoring points (M10) for wall and ceiling installation
- Full access to controls in all conditions of use
- 2-way 4 or 8 ohm available
- 10" custom B&C woofer with neodymium magnet ultra-light and ultra-powerful. Die-cast aluminium basket
- 1" Compression driver
- Internal Crossover with very high quality components and designed for the utmost resistance to vibration
- Drivers protected against overload and acoustic feedback
- Flat frequency response over the entire dispersion angle
- Recommended amplifier 250W Ohm
- SPL 121/124 dB
- Inputs panel with 2 Neutrik™ Speakon NL-4 connectors and links

FBTMaxX 2 - Specifications

Configuration	way	2
Recommended amplifier	W rms	250
Short term power (IEC 268-5)	W	500
Nominal impedance	Ohm	4/8
Frequency response	@-6dB	50Hz - 20kHz
Low frequency woofer	inch	1x10" - 2" Ø coil
High frequency driver	inch	1x1" + horn - 1,4" Ø coil
Sensitivity (@1W/1m)	dB	97
Maximum SPL	dB	121/124
Dispersion	H x V	90° x 60°
Crossover frequency	kHz	1,8
Recommended HP filter		...
Recommended external filter		...
Input connectors		2 x speakon
Net dimensions (WxHxD)	mm	352x550x307

Shipping weight	kg	13