

FBT MaxX 4A - Aktivni zvučnik

FBT MaxX 4A - Aktivni zvučnik

Šifra: 3712

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: FBT

Cena: **98.400,00** rsd

Processed Active Monitor 300+100W

- Extremely light and sturdy enclosure made of polypropylene with gas injection moulding
- Custom horn, handled and stand adapter built into the structure
- It can be used in all audio-professional amplification systems
- Asymmetric profile for use as a stage monitor
- Four anchoring points (M10) for wall and ceiling installation
- Provided with adapters to stack the enclosures
- Full access to controls in all conditions of use
- 2-way bi-amplification system:

woofer with power stage of 300W rms with PWM "Pulse Width Modulation" technology,

driver/horn with power stage of 100W rms in class AB

- 320 mm custom B&C speaker with neodymium magnet, ultra-light and ultra powerful. Die-cast aluminium basket

- 1" compression driver

- ADAP ® (Advanced Dynamic Active Protection) processor for total transducer protection and optimizing acoustic response. It guarantees total reliability even under the harshest conditions (prolonged Larsen effect)

- Active electronic filter (24 dB/oct.)

- Highly professional control panel with XLR/Jack Neutrik TM, input - XLR Neutrik TM, Link - Gain plus Mic/Line selector, 3-band equalizer (High-Mid-Low), Volume

FBTMaxX 4A - Specifications

Configuration	way	2
Built-in amplifier	W rms	300+100
Frequency response	@-6dB	50Hz - 20kHz
Low frequency woofer	inch	1x12" - 2,5" Ø coil
High frequency driver	inch	1x1" + horn - 1,4" Ø coil
Sensitivity (@1W/1m)	dB	98
Maximum SPL	dB	123
Dispersion	H x V	90° x 60°
Input impedance	kOhm	22
Crossover frequency	kHz	active 1,8
Input connectors		combo / XLR M
Power cord	m	5
Net dimensions (WxHxD)	mm	407x634x330
Net weight	kg	16
Shipping dimensions (WxHxD)	mm	510x740x410