**OGO**e not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

File Mittursuld 5 Atype unknown

The

## FBT Mitus 115A

Šifra: 7746

Kategorija prozivoda: Aktivne Zvučne Kutije

Proizvođač: FBT

Cena: 215.880,00 rsd

# Mitus 115a - 600W + 300W 133DB SPL PROCESSED ACTIVE SPEAKER

The MITUS 115 A is a 2-way design active speaker, with a 15" neodymium magnet woofer and a 1.7" VC HF compression driver, both by B&C, mounted on a 80°H x 50°H rotatable CD horn. The Class D amplifiers with switch mode power supply provide 600w RMS LF and 300w RMS HF. The Mitus 112A

features a DSP with 8 factory presets to provide the best performance for numerous applications. The New MITUS 115 A features a Baltic birch plywood cabinet, with a heavy duty grille and with a dust/moisture protection foam backing. Completely Made In Italy

## THE FBT MITUS - Setting a New Milestoner,

performance, weight, flexibility and ease of use, the new MITUS sound reinforcement series is the true result of our experience and passion for excellence. High quality B&C neodymium magnet woofers, custom manufactured for FBT. The latest generation of B&C compression drivers. High efficiency Class D power amplifiers modules with switch mode power supplies, Neutrik Powercon IN and LINK OUT power receptacles DSP with A/D-D/A low noise converters providing crossover, equalization, system protection along with 8 selectable presets.

5 different configurations allowed, suspended or ground stacked. A wide range of accessories makes the MITUS range extremely flexible for live or permanent installations. A comprehensive range of line array systems, speakers, subwoofers and monitor systems, available in active or passive design, to deliver the finest sound in all applications, from touring to permanent installation.

Die-cast aluminum chassis. New aluminum die-cast carrying handles. Heavy duty metal grille with anti-resonance spacers and FBT exclusive synthetic cloth.

#### **FEATURES**

2-way, bi-amplified, bass-reflex design

25 mm (1") exit B&C neodymium magnet HF driver with 44 mm (1.7") voice coil with 80°H x 50°V rotatable horn

Frequency response from 46Hz to 20KHz

15 mm (5/8") birch plywood enclosure, scratch resistant black paint finish

Ideal for live sound reinforcement applications as front of house main PA. Also suited for permanent installations

380 mm (15") B&C neodymium magnet woofer with 75

mm (3") voice coil

Class D built-in amplifiers, 600WRMS to the LF and 300WRMS to the HF, switch mode power supply Control panel with XLR input and link, volume, presets,

HP-filter, ground-lift

Eight M10 fly points, 35 mm (1.38") speaker stand socket and two FBT design aluminium handles

Very lightweight, only 28Kg

### SPECSIFICATION

Depth: 16.6 in Height: 29.5 in Width: 16.7 in

Product Weight: 61.7 lbs Shipping Weight: 67.3 lbs Current Draw: 640 Watt AC Voltage: 120 Volts Depth: 421 mm Height: 750 mm Width: 425 mm

Product Weight : 28 kg Shipping Weight : 30.5 kg

SPL Max: 133 dB

Frequency Response : 46Hz-20kHz

Power Output: 600w RMS LF, 300w RMS HF

