

FBT Mitus 115A

Šifra: 7746

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: FBT

Cena: 215.880,00 rsd

features a DSP with 8 factory presets to provide the best performance for numerous applications. The New MITUS 115 A features a Baltic birch plywood cabinet, with a heavy duty grille and with a dust/moisture protection foam backing. Completely Made In Italy

THE FBT MITUS - Setting a New Milestone

Advancing the concept of line arrays in terms of power, performance, weight, flexibility and ease of use, the new MITUS sound reinforcement series is the true result of our experience and passion for excellence. High quality B&C neodymium magnet woofers, custom manufactured for FBT. The latest generation of B&C compression drivers. High efficiency Class D power amplifiers modules with switch mode power supplies, Neutrik Powercon IN and LINK OUT power receptacles DSP with A/D-D/A low noise converters providing crossover, equalization, system protection along with 8 selectable presets.

5 different configurations allowed, suspended or ground stacked. A wide range of accessories makes the MITUS range extremely flexible for live or permanent installations.

FEATURES

2-way, bi-amplified, bass-reflex design
25 mm (1") exit B&C neodymium magnet HF driver with 44 mm (1.7") voice coil with 80°H x 50°V rotatable horn
Frequency response from 46Hz to 20KHz
15 mm (5/8") birch plywood enclosure, scratch resistant black paint finish
Ideal for live sound reinforcement applications as front of house main PA. Also suited for permanent installations

SPECSIFICATION

Depth : 16.6 in
Height : 29.5 in
Width : 16.7 in
Product Weight : 61.7 lbs
Shipping Weight : 67.3 lbs
Current Draw : 640 Watt
AC Voltage : 120 Volts

FBT Mitus 115A
Image not found or type unknown

The

Mitus 115a - 600W + 300W 133DB SPL PROCESSED ACTIVE SPEAKER

The MITUS 115 A is a 2-way design active speaker, with a 15" neodymium magnet woofer and a 1.7" VC HF compression driver, both by B&C, mounted on a 80°H x 50°H rotatable CD horn. The Class D amplifiers with switch mode power supply provide 600w RMS LF and 300w RMS HF. The Mitus 112A

A comprehensive range of line array systems, speakers, subwoofers and monitor systems, available in active or passive design, to deliver the finest sound in all applications, from touring to permanent installation.

Die-cast aluminum chassis. New aluminum die-cast carrying handles. Heavy duty metal grille with anti-resonance spacers and FBT exclusive synthetic cloth.

380 mm (15") B&C neodymium magnet woofer with 75 mm (3") voice coil

Class D built-in amplifiers, 600WRMS to the LF and 300WRMS to the HF, switch mode power supply

Control panel with XLR input and link, volume, presets, HP-filter, ground-lift

Eight M10 fly points, 35 mm (1.38") speaker stand socket and two FBT design aluminium handles

Very lightweight, only 28Kg

Depth : 421 mm

Height : 750 mm

Width : 425 mm

Product Weight : 28 kg


Shipping Weight : 30.5 kg

SPL Max : 133 dB

Frequency Response : 46Hz-20kHz

Power Output : 600w RMS LF, 300w RMS HF

Image not found or type unknown



Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.