

## FBT Mitus 118SA - Aktivni vufer

Šifra: 10311

Kategorija proizvoda: Aktivni Subwooferi

Proizvođač: FBT

**Cena: 191.880,00 rsd**



### 1200W 139dB SPL Processed Active Subwoofer

The MITUS 118 SA is single 18" active subwoofer equipped with a B&C neodymium magnet custom woofer.

The birch-ply enclosure is designed to the same width size of the MITUS 206 LA line array, like the MITUS 121 SA, 21" active sub and the MITUS 212 FSA flying active sub. This model has a band-pass design providing more "kick" to the low frequencies, extended down to 36 Hz. The built-in amp is engineered in Class D with DSP and supplies 1200 Wrms of continuous power. A switch mode power supply guarantees the maximum energy and dynamics to the transducer.

#### THE FBT MITUS - Setting a New Milestone

Advancing the concept of line arrays in terms of power, performance, weight, flexibility and ease of use, the new MITUS sound reinforcement series is the true result of our experience and passion for excellence. A comprehensive range of line array systems, speakers, subwoofers and monitor systems, available in active or passive design, to deliver the finest sound in all applications, from touring to permanent installation. High quality B&C neodymium magnet woofers, custom manufactured for FBT. The latest generation of B&C compression drivers. High efficiency Class D power amplifiers modules with switch mode power supplies, Neutrik Powercon IN and LINK OUT power receptacles DSP with A/D-D/A low noise converters providing crossover, equalization, system protection along with 8 selectable presets. Die-cast aluminum chassis. New aluminum die-cast carrying handles. Heavy duty metal grille with anti-resonance spacers and FBT exclusive synthetic cloth. 5 different configurations allowed, suspended or ground stacked. A wide range of accessories makes the MITUS range extremely flexible for live or permanent installations.

#### Mitus 118SA

##### FEATURES

- 1200W - 139dB SPL Processed Active Subwoofer
- Compact vented band pass subwoofer design enclosure
- 460 mm (18") custom B&C neodymium magnet high excursion woofer with 75 mm (3") voice coil
- Frequency response from 36Hz to 100Hz
- Class D amplifier delivering 1200WRMS
- Switch mode power supply
- DSP with 8 presets, cardioids and infra configurations, delay
- Control panel with XLR input and link, volume, presets, delay, phase 0°-180°, groundlift
- 18 mm (3/4") birch plywood enclosure, scratch resistant black paint
- Eight M10 fly points, M20 top mount stand socket and two FBT design aluminum handles
- Optional 4 swivel-mount casters 80 mm (3.15") on request
- Perfect low-frequency extension for the MITUS range and an ideal companion for the MITUS 206LA line array for ground stack applications with optional MTB206 metal base

##### SPECS

1200w RMS : Class D amp w/ switch mode Power Supply

Frequency Response : 36Hz-100Hz @-6dB  
Maximum SPL : 139 dB  
Dimensions : 24"wx24.75hx30.4"d  
Net Wt. : 103 Lbs.  
Depth : 28.7 in  
Depth : 730 mm  
Height : 23.4 in  
Height : 594 mm  
Width : 22.6 in  
Width : 574 mm  
Product Weight : 103.6 lbs  
Product Weight : 47 kg  
Shipping Weight : 123.9 lbs  
Shipping Weight : 56.2 kg  
Current Draw : 640 Watt  
SPL Max : 139 dB

