

## FBT Mitus 206LA - Aktivni zvučnik

Šifra: 10312

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: FBT

**Cena: 179.880,00 rsd**

DSP, granting 600 Watts rms to the LF and 300 Watts rms to the HF. Ideal for small to medium sized applications, from multiple cabinet line arrays to single pole-mounted loudspeakers the MITUS 206 LA is equipped with 2x6.5" B&C neodymium woofers and 1.4" exit B&C neodymium compression driver mounted on a 100°H waveguide

Showcased at the 2010 Winter NAMM show, the [FBT](#) Mitus 206 LA is a two-way, compact, self-powered line array system with extended performance in the mid and high frequencies.

Intended for small to medium sized applications, and with multiple cabinet line arrays to single pole-mounted loudspeakers, the Mitus 206 LA is equipped with 2 x 6.5-inch B&C neodymium woofers and a 1.4-inch-exit B&C neodymium compression driver mounted on a 100-degree (H) waveguide.

It also incorporates a class D amplifier design, with digital signal processing, that delivers 600 watts (RMS) to the LF and 300 watts (RMS) to the HF. A strong but light-weight switch mode power supply provides high reliability.

The Mitus 206 LA enclosure is constructed from high-impact polypropylene and incorporates integrated line array rigging hardware. The maximum vertical dispersion of each module is 10 degrees, depending on the number of elements combined in the array.

A rigid metal grille backed by a foam protects the transducers from wear.

It can be configured using the new flyable Mitus 212 FSA (2 x 12-inch) active subwoofer or ground stacked on the Mitus 121 SA (1 x 21-inch) and 118 SA (1 x 18-inch) powered subwoofers.

2 x 6.5" (165 mm) B&C neodymium woofers with 1.7" (44 mm) coil

Frequency response from 68Hz to 20KHz

DSP on-board with 8 presets, +/- 5db HF level control for accurate amplitude shading

100° horizontal waveguide with very low distortion and near flat wavefront up to 18Khz  
Ideal for small to medium sized application, from single pole mounted loudspeakers with 100°H x 10°V coverage to multiple cabinet full sized line array, the MITUS 206LA maybe used also in outdoor applications where the system is not directly exposed to the elements

Very lightweight, only 14Kg

[Download PDF drawing](#)

[Download Configurations](#)

FBT Mitus 206LA - Aktivni zvučnik

**600W + 300W - 134dB SPL**  
**Active precision coverage**  
**vertical array**

**MITUS 206 LA** is a 2-way compact line array system boasting an extended performance in the mid and high requencies thanks to the original technology applied, matched with the latest Class D pulse width modulation built-in bi-amp system with

1.4" (36 mm) exit B&C neodymium driver with 2.5" (64 mm) coil

Latest class D built-in amplifiers, 600Wrms to the LF and 300Wrms to the HF with switch mode power supply

Control panel with XLR input and link, volume, presets, HF level, HP-filter, ground-lift

High impact polypropylene gas-injected enclosure with integrated rigging hardwareadjustable with 0° to 10° angle between cabinets at2° step

Wide range of hardware accessories for flying and ground stacked configurations

