

## FBT PROMAXX 112A - Aktivni zvučnik

FBT PROMAXX 112A - Aktivni zvučnik

### Common features:

Šifra: 13265  
 Kategorija proizvoda: Aktivne Zvučne Kutije  
 Proizvođač: FBT

**Cena: 81.480,00 rsd**

Biamped: 700W RMS LF, 200W RMS HF, power amplifiers in Class D for LF and in Class H/AB for HF with switch mode power supplies

Control Panel features balanced XLR/Jack input, XLR LINK OUT, 2 x Volume, RCA Stereo input, DSP display with rotative encoder and push

90°H x 60°V constant directivity horn

2-way, bi-amplified, bass reflex design cabinet

Digital signal processor with graphic display

2 x M10 suspension points, 35 mm (1,3/8") top-hat speaker stand socket, wall bracket mount flange plate

Front of House or Stage Floor Monitor: with 12°, 40° and 55° monitoring angles

### Specifications:

320mm (12") LF woofer with 64mm (2.5") voice coil, custom made for FBT

Frequency response from 48Hz to 20KHz

Extremely light only 14.8Kg/32.62lb

25mm (1") exit throat B&C HF magnet compression driver with 34mm (1.4") voice coil

Sturdy, gas-injected polypropylene molded enclosures, engineered to contain undesired resonance

Code:	40604
Configuration:	2 way
Built-in amplifier LF/HF:	700/200 W RMS
Built-in amplifier peak LF/HF:	1400/400 W
Frequency response:	48Hz - 20KHz -6dB
Low Frequency woofer:	12 - 2.5 coil inch
High Frequency driver:	1 - 1.4 coil inch
Maximum SPL cont/peak:	126/133 dB
Dispersion:	90° x 60° HxV
Input impedance:	22 Kohm
AC Power requirements:	640 VA
Input connector:	XLR with loop RCA ST
Power cord:	5/16.4 m/ft
Net Dimension (WxHxD):	402x644x345 / 15.8x25.4x13.6 mm/inch
Net Weight:	14.8/32.62 Kg/lb
Transport Dimension (WxHxD):	500x745x440 / 19.7x29.3x17.3 mm/inch