

FBT PROMAXX 112A

Šifra: 13265
Kategorija proizvoda: Aktivne Zvučne Kutije
Proizvođač: FBT

Cena: **95.880,00 rsd.**



Common features:

2-way, bi-amplified, bass reflex design cabinet

Biamped: 700W RMS LF, 200W RMS HF, power amplifiers in Class D for LF and in Class H/AB for HF with switch mode power supplies

Control Panel features balanced XLR/Jack input, XLR LINK OUT, 2 x Volume, RCA Stereo input, DSP display with rotative encoder and push

90°H x 60°V constant directivity horn

Digit

2 x M
speak

Front
55° m

Specifications:

320mm (12") LF woofer with 64mm (2.5") voice coil, custom made for FBT

25mm (1") exit throat B&C HF magnet compression driver with 34mm (1.4") voice coil

Sturdy, gas-injected polypropylene molded enclosures, engineered to contain undesired resonance

Frequ

Extre

Code:	40604
Configuration:	2 way
Built-in amplifier LF/HF:	700/200 W RMS
Built-in amplifier peak LF/HF:	1400/400 W
Frequency response:	48Hz - 20KHz -6dB
Low Frequency woofer:	12 - 2.5 coil inch
High Frequency driver:	1 - 1.4 coil inch
Maximum SPL cont/peak:	126/133 dB
Dispersion:	90° x 60° HxV
Input impedance:	22 Kohm
AC Power requirements:	640 VA
Input connector:	XLR with loop RCA ST
Power cord:	5/16.4 m/ft
Net Dimension (WxHxD):	402x644x345 / 15.8x25.4x13.6 mm/inch
Net Weight:	14.8/32.62 Kg/lb
Transport Dimension (WxHxD):	500x745x440 / 19.7x29.3x17.3 mm/inch
Transport Weight:	17.8/39.24 Kg/lb