


FBT PROMAXX 114A - Aktivni zvučnik

Šifra: 13266

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: FBT

Cena: 143.880,00 rsd



Common features:

2-way, bi-amplified, bass reflex design cabinet

Biamped: 700W RMS LF, 200W RMS HF, power amplifiers in Class D for LF and in Class H/AB for HF with switch mode power supplies

Digital signal processor with graphic display

Control Panel features balanced XLR/Jack input, XLR LINK OUT, 2 x Volume, RCA Stereo input, DSP display with rotative encoder and push

2 x M10 suspension points, 35 mm (1,3/8") top-hat speaker stand socket, wall bracket mount flange plate

90°H x 60°V constant directivity horn

Front of House or Stage Floor Monitor: with 12°, 40° and 55° monitoring angles

Specifications:

355 mm (14") LF neodymium magnet woofer with 75mm (3") voice coil, custom made for FBT by B&C

35 mm (1,4") exit throat B&C HF compression driver with 64 mm (2,5") voice coil

Frequency response from 45Hz to 20 kHz

Compact Dimensions: ProMaxX 114A uses the same size gas-injected polypropylene molded enclosure as the ProMaxX 112A, but features our 14" LF Woofer for lower frequency SPL

Full grille design with black acoustic cloth

Extremely light, only 17,4 kg / 40.78 lb

Code:	40603
Configuration:	2 way
Built-in amplifier LF/HF:	700/200 W RMS
Built-in amplifier peak LF/HF:	1400/400 W
Frequency response:	45Hz-20KHz -6dB
Low Frequency woofer:	14 - 3 coil neodymium inch
High Frequency driver:	1.4 - 2.5 coil inch
Maximum SPL cont/peak:	127.5 / 135.5 dB
Dispersion:	90° x 60° HxV
Input impedance:	22 Kohm
AC Power requirements:	IEC VA
Input connector:	XLR with loop, RCA ST

Power cord:	5/16.4 m/ft
Net Dimension (WxHxD):	402x644x345 / 15.8x25.4x13.6 mm/inch
Net Weight:	17.5/40.78 Kg/lb
Transport Dimension (WxHxD):	500x745x440 / 19.7x29.3x17.3 mm/inch
Transport Weight:	20.1/44.31 Kg/lb