

FOCAL Chorus 605 Black Ash

FOCAL Chorus 605 Black Ash

Šifra: 12706

Kategorija proizvoda: Bookshelf Zvučnici

Proizvođač: Focal

Cena: **19.080,00** rsd

Polyglass cone

A RICH MIDRANGE

Polyglass technology, exclusive to Focal, consists in applying molten glass microballs on a cellulose pulp cone. This process combines an excellent paper damping with glass rigidity. The mass/rigidity/damping ratio adjustment results in outstanding linearity of the frequency response curve, all from the inherent design of the cone. This innovation also greatly increases definition in the midrange.

TNV2 tweeter

A PRECISE AND SMOOTH SOUND

The TNV2 tweeter features a structure of the suspension which directly comes from the speakers of the reference Utopia line! The material used is very light which means that the suspension will not become damaged or compressed with time, the distortion will be reduced and the frequency response will be improved. The result is a sound which is soft and precise and which offers improved harmonics richness and a more precise soundstage.

Chorus design codes

MODERNISED AESTHETICS

You will find the elements which enabled the success of this range, such as the flawless cabinet-making techniques, the non-parallel side panels, the thick front and the many efficient reinforcement. You will then appreciate the subtle reinterpretation of the original design: The vivid and prominent lines have been replaced with smoother, more fluid curves to keep up to date with current trends. The quality of the assembly smoothens out the creases, and the choice of materials gives the speakers a sense of harmony and elegance.

Finishes

FRENCH ELEGANCE

Made in France, the Chorus 600 line is available in Black Style finish which The combination of the leather-covered enclosure and the black. The extremely appealing design has an elegant and timeless look.

Type

2 - way bass reflex bookshelf loudspeaker

Drivers

5" (13cm) Polyglass midbass

1" (25mm) TNV2 Al/Mg inverted dome tweeter

Frequency response (+/- 3dB)

65Hz - 28kHz

Low frequency point - 6dB

57Hz

Sensitivity (2.83V / 1m)

89dB

Nom. impedance

8 Ohms

Minimum impedance

3 Ohms

Recommended amplifier power

25 - 100W

Crossover frequency

3000Hz

Dimensions (HxLxP)

315x190x227mm

Net weight

5.7kg