

FOCAL Chorus 726 Blackstyle

Šifra: 11362

Kategorija proizvoda: Podnostojeći Zvučnici

Proizvođač: Focal

Cena: **67.080,00 rsd.**




The new Poron suspension softens the audio performance of the TNV2 tweeters. This innovation by Focal enables the perfect reproduction of the midrange and real dynamics of high frequencies. Heir to the Chorus 726 V, the Chorus 726 represents the affordable traditional high-end speaker. Entirely redesigned, the cabinet and the new grille give these speakers a sleek modern look, making them blend in perfectly with your interior.



TN2 Tweeter

Thanks to our constant improvement policy, the performance of the new TNV2 tweeter has been increased significantly compared its predecessor. The structure of the suspension comes directly from the speakers of the reference Utopia line! Its uniform and constant physical properties ensure excellent dimensional stability, which is a fundamental criterion when the design requires extreme accuracy.



Polyglass Cone

The Polyglass cone has been a Focal tradition for the last 30 years. Incessantly improving, it has matured today to a very high level of performance. The cellulose fibre cone offers renowned lightness and damping characteristics, but our special surface treatment of silica micro-balls gives the cone a huge increase in rigidity for a negligible increase in mass. The definition and dynamic capacity of this cone, when combined with a very powerful magnet (another Focal tradition), generates a very fine reproduction, with an exceptionally rich midrange.



Chorus Design

An elaborate and intricate cabinet design requires true expertise. Constructed from MDF, up to 25mm thick, with internal reinforcement fitted in the cable duct, nonparallel side panels... All of this expertise is the result of over 30 years experience.

Type

3-way bass-reflex bo

Speaker drivers

2 x 6 1/2" (16.5cm) P

(25mm) Al/Mg TNV2 i

Frequency response (+/- 3dB)

49Hz - 28kHz

Low frequency point - 6dB

39Hz

Sensitivity (2.83V/1m)

91.5dB

Nominal impedance

8 Ohms

Minimum impedance

2.9 Ohms

Recommended amplifier power

40 - 250W

Crossover frequency

300Hz/3000Hz

Dimensions (HxWxD)

989 x 222 x 345mm

Weight

51.7 lbs (23.5kg)