

## FOSTEX 6301NX

Šifra: 10817

Kategorija proizvoda: Aktivni Studijski Monitori

Proizvođač: FOSTEX

**Cena: 63.480,00 rsd**



The front panel provides a power switch and a rotary level control for easy volume adjustments. An automated protection circuitry prevents overloads and short circuits, while the die-cast aluminum enclosure is made to withstand the rigors of professional use. The 6301NX ships with a standard IEC power cord.

Compact aluminum design

4" full-range driver

20W Class-D amplifier for powerful performance

Transformer balanced XLR input

1/4" unbalanced input

Front-panel rotary volume control

Protection circuitry keeps the speaker operating smoothly

Magnetically shielded for safe use near video monitors

Multi-voltage power supply

Auto Standby Mode engages after 25 minutes, power consumption reduced to 0.5W

Optional bracket available separately for mounting

Type	Sealed powered speaker system
Speaker	Cone Type Driver: 4" / 102 mm
Amplifier	20 W Class-D
Frequency Range	70 Hz to 15 kHz
Output Sound Pressure Level	85 dB/W @ 1 m
Maximum Output	Maximum SPL: 98 dB
Rated Output	20 W
THD	0.05% (at 1 kHz 1 W output)
Input Terminal	Input: 1/4" TS, unbalanced Input: Analog balanced XLR, 3-31 type HOT No. 2 / transformer type
Input Impedance	Analog Input: 10 kOhms or More
Input Sensitivity	Analog (Unbalanced): -14 dBV (0.2 VRMS) Analog (Balanced): +4 dBu (1.2 VRMS)
Residual Noise	-70 dBV
Controls	1 x Power switch 1 x Volume control

Indicator LEDs	Unlit: Power off Lit In Green: Power on Lit In Red: In standby
Enclosure Material	Aluminum die-casting
Shielded	Yes
Power Consumption	Power Consumption: 10 W Auto Standby: 0.5 W
Dimensions (HxWxD)	7.4 x 4.7 x 4.7" / 189.0 x 120.0 x 120.0 mm
Weight	4.9 lb / 2.2 kg