

FOSTEX PX-5

Šifra: 10658

Kategorija proizvoda: Aktivni Studijski Monitori

Proizvođač: FOSTEX

Cena: **29.880,00** rsd

Drivers driven by a 35W (LF) / 18W (HF) digital amplifier

5.2-inch Crimson woofer constructed of aramid fiber with mixed diaphragm impregnated with resin to enhance fiber bonding for higher rigidity

1-inch Urethane film laminated polyester fiber dome tweeter tuned with the back chamber for smooth high frequency sonics

Digital Network Filter (FIR type) for dividing network - results in very accurate time alignment to deliver supreme sound positioning

Unique Rotary Encoder plus LED indication with no aging quality deterioration

44 step level control by Volume/Trim adjustments

+/-3dB per 0.3dB step HF level control and +/- 20 step LF roll off frequency adjustment

Auto Standby / Auto Operation function for electric power saving

Fade In function to gradually increase the output level when powering on

Specifications

SPEAKER SECTION

Enclosure type: 2 way bass reflex

Units

Tweeter: 1-inch soft dome tweeter

Woofer: 5.2-inch Aramid fiber diaphragm

Frequency Response: 50 Hz – 20k Hz

AMPLIFIER SECTION

Rated Output Power Low: 35W High: 18W

Inputs: XLR-3-31 connector (balanced)

Maximum input level: +24 dBu

Input Impedance: 20k ohm or more

1/4-inch Phone jack (unbalanced)

Maximum input level: +10 dBV

Input Impedance: 10k ohm or more

RCA jack (unbalanced)

Maximum input level: +10 dBV

Input Impedance: 10k ohm or more

*XLR-3-031 connector and 1/4-inch phone jack are combined in the combo con-nectector

S/N Ratio: 96 dB

Distortion (T.H.D.): 0.2%

Crossover Frequency: 2.5 kHz

Subsonic filter: 50 Hz

GENERAL

Dimensions: 280 (H) x 180 (W) x 210 (D) mm

Weight: 5 kgs

Power Requirement:

US: 120 VAC, 60Hz

EUR/UK: 230 VAC, 50/60Hz

Power Consumption: 50 W (0.5W or less in standby mode)

Specifications and appearance are subject to change without notice