

logo not found or type unknown

Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

## INVISION iMove 200SR - Roto glava

---

Šifra: 03135  
Kategorija proizvoda: Roto Glave  
Proizvođač: INVISION

**Cena: 35.880,00 rsd**

### INVISION iMove 200SR - Roto glava

Image not found or type unknown



## iSolution HID-150 iMove 200SR

iSolution technology allows synchronisation of different types of intelligent iSolution fixtures via either a custom-built iLead DMX-512 controller or in stand-alone mode. iLead (Integrated Lighting System) allows fixtures to be linked and work in synchronisation, regardless of type, including iLead-equipped scanners, moving heads, and colour changers. The iLead controller can also remotely set the DMX addresses of the fixtures. All units are also controllable via any universal DMX-512 controller. Conversely, the iLead controller is a universal DMX-512 controller and can be used with non-iSolution fixtures.

**Control:** DMX 512 - 8 channels

Setting and addressing : 4 digit LED display. LED display with on/off setting function.

Data in/out: Locking 3-pin XLR

iSolution operation: Consistent DMX configuration enables iMove to be linked with iRock and iShow. DMX address can be set remotely by iLead controller. No need to calculate the DMX channels of each fixture in the chain. When the DMX signal is off, the lights will switch to Master/Slave mode automatically.

Easy installation, easy addressing, and easy operation.

Pre-programmed function

Automatic switching between music trig or auto trig mode

Master/ Slave mode Built in dynamic lighting shows for instant operation.

User friendly Easy Controller: Enjoy many lighting shows at your fingertips.

Pan: 540 degrees ;

Tilt: 270 degrees 11 trapezoid dichroic colours + white, rainbow effect 8 interchangeable rotating gobo's plus white Blackout, 0-100% dimmer and high speed variable strobe

High quality optical lens, dichroic colors and gobo's.

Beam angle: 14 degrees

### **Specification:**

Power supply: 230v Lamp: HID 150w

Replacement lamp: Lamp88

Dimensions: 276 x 266 x 369mm

Weight: 10.0kgs