

MARTIN JEM ZR45 - Dim mašina

Šifra: 11436

Kategorija proizvoda: Dim Mašine

Proizvođač: Martin



Cena: 152.280,00 rsd

KARAKTERISTIKE

- Kompaktna i moćna
- Jednostavno plug-and-play podešavanje sa daljinskim upravljačem
- Za mobilnu upotrebu ili fiksnu instalaciju
- Podesiv izlaz dima
- Mala potrošnja tečnosti
- 2000 W grejač
- Maksimalna potrošnja: 210 ml/min
- Kapacitet rezervoara: 5 l kanister
- Efektivnost: 1300 m³/min
- Vreme zagrevanja: 10 minuta
- Digitalni žičani daljinski upravljač
- DMX and RDM
- Ulaz napajanja: Power Twist TR1 (uključujući 3 m kabl bez konektora)
- Kućište: aluminijum i čelik
- DMX ulaz i izlaz: 5-pinski XLR
- Napajanje: AC 220 - 240 V @ 50/60 Hz AC 220 - 240 V @ 50/60 Hz
- Potrošnja snage: 2100 W / 9.2 A
- Dimenzije sa nosačem (D x Š x V): 602 x 395 x 393 mm
- Težina (bez tečnosti):
- Uključuje nosač za montažu

Specifications

Physical

Length: 602 mm (23.1 in.)

Width: 395 mm (15.6 in.)

Height: 306 mm (12.1 in.)

Height with hanging bracket: 393 mm (15.5 in.)

Weight, dry: 17.7 kg (39.1 lbs.)

Weight, filled: 22.7 kg (50 lbs.)

Performance

Coverage volume: 1300 m³ (45,909 ft³) per minute

Fluid consumption (max.): 210 ml per minute

Maximum operating time, maximum output, 5 l of fluid: 1.18 hours

Ready time: 10-minutes

Continuous effect output

Control and Programming

Control options: Integrated digital remote control, DMX, master/client link mode

Control parameters: Continuous or timer-controlled output

Fog: Variable output control, 0-100%

DMX channels: 1

External fluid control: Fluid sensing

DMX compliance: ANSI E1.11 - USITT DMX512-A

RDM compliance: ANSI/ESTA E1.20 RDM

Construction

Housing: Steel and aluminum

Color: Black

Heat exchanger:

1800 W, thermally protected (US Model)

2000 W, thermally protected (EU Model)

Fluid pump: Dual oscillating piston, high pressure

Fluid management: Fluid out sensing, sealed for transportation

Fluid reservoir: 5 l drop-in reservoir with quick-connect fitting

Remote Control: Integrated Digital Remote with 3 m (9.84 ft.) cable, 3-pin XLR

External Fluid Control: Fluid sensing

Hanging bracket: Integrated yoke with safety attachment point

Installation

Mounting: Standing or hanging

Orientation: Up to +/-40° from horizontal

Clearance around machine: 100 mm (4 in.)

Connections

AC Power: Neutrik PowerCON TRUE1

DMX, link mode in/out: 5-pin locking XLR

Remote control: 3-pin locking XLR

Firmware: AVR socket

Electrical

EU Model:

AC power: 220-240 V AC nominal, 50/60 Hz

Typical current draw: 9.2 A @ 230 V *

Power Consumption

Typical: 2100 W *

US Model:

AC power: 100-130 V AC nominal, 50/60 Hz

Typical current draw: 15.0 A @ 110 V *

Power Consumption

Typical: 1800 W *

* Measurements made at nominal voltage. Allow for a deviation of +/- 10%.

Thermal

Maximum nozzle temperature: 290° C (554° F)

Maximum ambient temperature (Ta max.): 40° C (104° F)

Minimum ambient temperature (Ta min.): 5° C (41° F)

Exterior surface temperature, steady state: 30° C (86° F)

Approvals

EU safety: EN 60 335-1

EU EMC: EN 61000-6-3, EN 62233

EU immunity: EN 61000-6-1

US safety: UL 998

Canadian safety: CSA C22.2 No 104

Australia/NZ: RCM (pending)

United Kingdom: UKCA

Included Items

Fluid reservoir, 5 l: P/N 34300506

JEM ZR Series Integrated Digital Remote Control: P/N M55765048

Power input cable, EU, PowerCON TRUE1, stripped ends, 3 m (9.8 ft.): P/N 11501043

Power input cable, US, 20A, powerCON TRUE1, molded NEMA 5-20P, 2 m (6.6 ft.): P/N 11501046

Accessories

JEM ZR45 Ducting System with 5 m (16.4 ft.) 4" flexible ducting: P/N 92625014

JEM External Fluid Reservoir Kit, 25 l: P/N 92620035

Approved fluids*:

JEM Pro-Fog Fluid, Quick Dissipating

JEM Pro-Fog Fluid

JEM Pro-Fog Fluid, High Density

RUSH & THRILL Fog Fluid

Martin Pro-Clean and Storage Fluid

Approved discontinued fluids*:

Pro Smoke Studio (DX)

Pro Smoke Super (ZR)

Pro Smoke High Density (SP)

I-Fog Fluid

Regular DJ Fluid (DJ)

RUSH Fog Fluid

RUSH ELX Smoke Fluid

Martin Pro Clean Supreme

Service Tools:

Epsilon 5 AVR Programmer: P/N 50502004

Temperature Calibration Box: P/N 92620005