**logo**e not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

KalgeGidt30GR or type unknown

## KEF Ci130CR

Šifra: 10550

Kategorija prozivoda: Plafonski Zvučnici

Proizvođač: KEF

Cena: 13.320,00 rsd

All of Kef's CR are all circular in shape and made for flush mounting into ceiling voids or walls, the Ci series delivers KEF legendary quality as unobtrusively as possible featuring some of the thinnest bezels on the market. All of Kef's custom speaker models are designed to withstand a multitude of environments including bathrooms and under the eves outside.

The C series of custom speakers features KEF's unique asymmetrical tweeter island, this configuration reduces high frequency diffraction and aligns the off-axis power response of the tweeter and woofer to make the speaker almost as placement friendly as Uni-Q. Combining impeccable sound quality with the elegant ultra-thin bezel. With Kef's simple and ingenious mounting system, you'll also find them amazingly easy and rapid to install.

The Ci130CR delivers Hi-Fi quality sound through a polypropylene cone low frequency driver with a high frequency driver mounted at the acoustic centre of the LF drive unit. The bezel and grill can be painted to match the interior decor of the room.

## **Key Features**

10-80W
In Ceiling / In Wall Speaker
LF & HF Drive Unit
158mm cutout
Flush Wall Ceiling Fit
Ultra Thin Bezel
White Paintable Grills

## **Applications**

The Ci Series Ci130CR is best suited for high quality music and speech reinforcement applications requiring hi-fi performance such as:

Multi Room systems
Home Theatre systems
Lounges, Bars, Boutiques
Boardrooms & Offices
Airports, Convention Centres, Hotels
Live Theatre/Concert Hall fill-in
Houses of Worship

Driver diameters	LF 130mm Uni-Q + Integral 19mm HF
Recommended Amplifier Power	10-100w
Nominal impedance	8ohm
Sensitivity	87dB
Product External Dimensions (Diameter / Depth) type	193.4mm (7.61in.) / 83mm (3.28in.)
Cut-out Diameter	158mm (6.22in.)
Mounting Depth from Surface	77.8mm (3.06in.)
Frequency Response +/-6dB open backed	45Hz - 34kHz