

logo not found or type unknown

Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

# KEF CI200ER UNI-Q 2 WAY - Plafonski zvučnik

Šifra: 18521  
Kategorija proizvoda: HI-FI Ugradni Zvučnici  
Proizvođač: KEF

Cena: 14.280,00 rsd

KEF CI200ER UNI-Q 2 WAY - Plafonski zvučnik  
Image not found or type unknown

not seen, with unprecedented value and performance, KEF's Ci-E series of architectural speakers is designed and manufactured to the same exacting standards as all KEF's architectural offerings and features KEF's famed Uni-Q driver technology.

KEF's Uni-Q driver enables the mid-range and tweeter to act as a single point source. This patented technology allows the listener to sit anywhere in the room and still enjoy KEF's world-

renowned sound and clarity without having to be positioned in the narrow "sweet-spot" found with conventional speaker designs.

The Ci-E Series also features KEF's Ultra-Thin Bezel (UTB) technology which offers the thinnest possible visible rim around the speaker assembly. The bezel and grill can be painted to match the interior décor.

The speakers in the Ci-E Series, are manufactured to Weather Resistant Construction standards: The grilles are coated via a proprietary process, the speakers include moisture-resistant terminations and finish materials, and the plastics are UV protected, allowing you to safely use these speakers in applications such as bathroom and kitchen.

UTB™ Ultra Thin Bezel  
200mm (8in.) Uni-Q driver array  
16mm (0.6in.) Aluminium dome tweeter  
Weather Resistant  
Magnetic Grille

Nominal Impedance	8 Ohms
Sensitivity	90dB (2.83V/ 1m)
Frequency Response	45Hz - 20kHz (±6dB) open-backed
Crossover Frequencies	2.8kHz
Drive Units	
- LF	200mm (8in.)
- HF	16mm (0.6in.)
Recommended Amplifier Power	10-125W

<b>Product Dimensions</b>	
- Diameter	289.6mm (11.4in.)
- Depth	103.3mm (4.07in.)
<b>Cut-Out Dimensions</b>	
- Diameter	240mm (9.45in.)
<b>Mounting</b>	
- Ceiling Thickness (Maximum)	37mm (1.46 in.)
- Ceiling Thickness (Minimum)	6mm (0.24 in.)
- Mounting Depth From Surface	97.2mm (3.83in.)
<b>Optional Accessories</b>	
- Rough In Frame	RIF200R
- Rear Enclosure	RNC200R
<b>Other</b>	
- Net Weight	1.6kg (3.6lbs)
- Unit Measurement	Piece