

KEF Q550 Black Podnostojeći Zvučnik

Šifra: 12130

Kategorija proizvoda: Podnostojeći Zvučnici

Proizvođač: KEF

Cena: 65.880,00 rsd

KEF Q550 Black Podnostojeći Zvučnik

The Q550 is the smallest floorstander in the Q Series line. Featuring KEF's signature Uni-Q driver array paired with a 130mm (5.25 inch) aluminium bass driver and two matching ABRs, the Q550 delivers a phenomenal audiophile performance with clarity, scale, and controlled bass. Great for large or small rooms the Q550 is available in Satin Black or Satin White finishes.

"Sit anywhere" Uni-Q Sound

At the heart of the evolved Q Series is the Uni-Q driver array. KEF's signature innovation places the tweeter in the acoustic center of the midrange cone, bringing the acoustic ideal of a

single point source closer than ever to realization. The result is a more detailed, more accurate three-dimensional sound image, which is dispersed more evenly throughout the room than is possible with a conventional speaker. Uni-Q's ultra-wide dispersion is further enhanced by KEF's 'tangerine' waveguide over the tweeter dome.

Uni-Q sound taken to the next level

To optimize the resolution and purity of the Q Series bookshelf speakers, the Uni-Q driver has been repositioned to the center of the cabinet to reduce unwanted internal resonance and adds refinement to their sonic clarity and detail. With the addition of the Damped tweeter loading tube providing a gentle termination of sound produced from the back of the tweeter, lower treble performance is improved dramatically and a new low-distortion inductor on the crossover provides cleaner bass response.

CFD Designed Port

Featuring a Computational Fluid Dynamics (CFD) port design with the port repositioned to the rear of the speaker, clarity is improved by reducing the audibility of the midrange leakage through the port. The geometry of the ports have been tuned to minimize turbulence at higher levels resulting in a reduction in port noise and less LF compression.

SPECIFICATIONS

Model	Q550 Floorstanding Speaker
Design	Two and a half-way bass reflex
Drive Units	130mm (5.25in.) aluminum Uni-Q 25mm (1in.) vented aluminum dome HF 130mm (5.25in.) aluminum LF 2x 130mm (5.25in.) aluminum ABR
Frequency Range Free Field (-6dB)	45Hz
Frequency Response (±3dB)	58Hz - 28kHz
Crossover Frequency	2.5kHz
Amplifier Requirements	15-130W
Sensitivity (2.83V/1m)	87dB
Maximum Output	110dB
Nominal Impedance	8? (min.3.5?)
Weight	14.5kg (32 lbs)
Dimension (H X W X D)	873mm (34.37 inches) x 180mm (7.08 inches) x 278mm (10.94 inches)
Dimension (H X W X D) *with Rubber Feet	926mm (36.45 inches) x 299mm (11.77 inches) x 310mm (12.20 inches)