

KEF Q950 Black - Podnostojeći Zvučnik

Šifra: 12132

Kategorija proizvoda: Podnostojeći Zvučnici

Proizvođač: KEF

Cena: 83.880,00 rsd

KEF Q950 Black - Podnostojeći Zvučnik

KEF

Q950 Speakers (Pair) embody the Q-Series' innovative vision with a Uni-Q driver, 200mm long-throw bass driver and a sophisticated aesthetic. An updated version of the earlier Q900, the Q950 out-performs its successor with its intricately detailed and clear high-resolution sound quality.

Placed above the Q750 and Q550, the Q950 is the flagship floorstanding model in the Q-Series.

Detailed and Even Sound Image

The Uni-Q driver array epitomises the high-calibre quality of the reborn Q Series. This cutting-edge innovation situates the tweeter in the acoustic middle of the midrange and bass cone, which brings the acoustic dream of a single point source closer than ever to reality.

Therefore you can immerse yourself in a highly detailed and accurately nuanced 3D soundscape. Even better, the sound is equally dispersed around the room, a feat not found in other speakers. The wide dispersion performance is accentuated by KEF's emblematic 'tangerine' waveguide.

Pristine Bass Performance

A brand new low-distortion inductor on the crossover offers a pristine bass performance. The lower treble performance of the Q950 is significantly improved thanks to the inclusion of the damped tweeter loading tube which provides a gentle finish to sound generated from the rear of the tweeter.

Enhanced Midrange Clarity

Enhanced clarity and a more exuberant bass performance are delivered by the closed box midrange cabinet design that minimises the force on the Uni-Q midrange cone.

Improvements to the mid-bass driver notably improve the clarity of the midrange, namely the elimination of the DC blocking capacitor. The removal of the capacitor also ensures a smoother bass roll-off between the Q950's drivers.

Tech Specs

- Model: Q950
- Design: Two and a half-way bass reflex
- Drive Units: 200mm aluminium Uni-Q, 38mm vented aluminium dome HF, 200mm aluminium LF
- 2 x 200mm aluminium ABR
- Frequency Range Free Field: 38Hz (-6dB)
- Frequency Response: 44Hz-28kHz (±3dB)
- Crossover Frequencies: 2.2kHz
- Maximum Output: 113dB
- Amplifier Requirements: 15-200W
- Sensitivity: 91dB (2.83V/1m)
- Nominal Impedance: 8 Ohms (min.3.2 Ohms)
- Dimensions (H x W x D): 1062 x 244 x 328 mm
- 1116 x 357 x 328 mm (with Plinth)
- Weight: 20.6kg
- Unit Measurement: Pair