

KLIPSCH R 24F

Features:

Šifra: 12744
Kategorija proizvoda: Podnostojeći Zvučnici
Proizvođač: Klipsch

Cena: 29.880,00 rsd

Dual 4.5" copper-spun, high-output IMG woofers

Dynamic aluminum Linear Travel Suspension horn-loaded tweeter
Brushed black polymer veneer cabinet

1" Horn-Loaded Tweeter: The R-24F floorstanding speaker features Klipsch's proprietary Tractrix Horn technology mated with a 1" aluminum LTS tweeter, for impressive high-end response and greater extension, enhanced imaging and powerful dynamics.

Tractrix Horn Technology: The square Tractrix Horn delivers a 90° (w) x 90° (h) dispersion pattern for a broader sound-stage.

LTS (Linear Travel Suspension): Behind each horn lies a 1.0-inch aluminum tweeter with a linear travel suspension to minimizes distortion for enhanced, detailed performance.

Dual 4.5" Copper-Spun IMG Woofers: The Klipsch R-24F floorstanding speaker is outfitted with two 4.5" Copper-Spun IMG woofers. The Copper-Spun IMG (Injection Molded Graphite) woofer is exceptionally light while being extremely rigid - providing remarkable low frequency response, with minimal cone breakup and distortion.

Front-Firing Port: The Klipsch Reference series floorstanding speaker features a front-firing port that is perfectly matched to the cabinet and drivers. The front placement of the port creates ideal airflow with minimal distortion.

MDF Cabinet: The Klipsch R-24F floorstanding speaker features a MDF cabinet with a brushed polymer veneer black finish that seamlessly integrates into almost any room or decor. MDF (Medium Density Fiberboard) is utilized because of its damping characteristics for natural, uncolored sound without unwanted vibration and distortion.

Acoustically Transparent Grille: The Klipsch R-24F floorstanding loudspeaker comes with a removable, black cloth grille that is acoustically transparent.

Dual 5-Way Binding Posts: The Klipsch Reference series floorstanding speaker is fitted with two sets of 5-way binding posts connected by jumpers. Using the dual binding posts, you can bi-amp or bi-wire the speakers. The binding post terminals will accept banana plugs (single or dual), pin-connectors, spade-lugs, and bare wire (up to 10AWG).

Integrated Rubber Feet: The Klipsch R-24F floorstanding speaker features four integrated rubber feet for placing the speaker securely and safely on your hardwood, laminate, or tile floor (these rubber feet should never be removed). The floorstanding speaker does not come with any carpet spikes.

Placement: For optimum performance, Klipsch suggests placing the floorstanding speakers 6' to 15' apart. They may also be toed-in slightly for better stereo imaging. The listening position should be about 1 to 1.5x the distance separating the speakers.

Reference Series: The Klipsch Reference series consists of three floorstanding speakers (R-24F/R-26F/R-28F), two bookshelf speakers (R-14M/R-15M), one center channel speaker (R-25C), and one surround speaker (R-14S). The Klipsch Reference series line-up of loudspeakers sound great in stereo and home theater applications.

| SPECIFICATIONS | |
|----------------------|---------------------------------------|
| FREQUENCY RESPONSE | 45 - 24k +-3dB |
| SENSITIVITY | 95dB @ 2.83V / 1m |
| POWER HANDLING | 75W RMS / 300W Peak |
| NOMINAL IMPEDANCE | 8 Ohms Compatible |
| HIGH FREQUENCY HORN | 90º x 90º Tractrix Horn |
| LOW FREQUENCY DRIVER | Two 4.5" (25.4cm) IMG woofers |
| CROSSOVER | 1600Hz |
| ENCLOSURE TYPE | Bass-reflex via front firing port |
| INPUT TYPE | Dual Binding Posts / bi-wire / bi-amp |
| HEIGHT | 34.75" (88.27cm) with feet |
| WIDTH | 6.5" (16.51cm) |
| DEPTH | 10" (25.4cm) with grille |
| WEIGHT | 25lbs (11.34kg) |
| FINISH | Brushed Black Polymer Veneer |
| BUILT FROM | 2015 |