

KLIPSCH R-51PM

Šifra: 13309
Kategorija proizvoda: Wireless Zvučnici
Proizvođač: Klipsch

Cena: **59.880,00** rsd

SOUND THAT PACKS A PUNCH

A truly powerful, small form-factor music monster packed with Klipsch acoustics with integrated power and Bluetooth® wireless technology.

DESIGNED FOR SIMPLE SET UP WITH YOUR TURNTABLE, TV, COMPUTER OR WIRELESS DEVICE

With an integrated phono pre-amp, Bluetooth® wireless technology, digital optical, analog RCA and USB inputs, your R-51PM is the best performing, most versatile monitor on the planet.

DYNAMIC BASS EQ

As the human ear perceives frequencies differently with variations in output, the R-51PM will dynamically match the ear's ability to hear lower frequencies. Typically, only available with audio/video receivers, dynamic volume is a first for Klipsch powered monitors. What you get is powerful bass whether the listening volume is low, cranked up or somewhere in between.

HIGH EFFICIENCY AMPLIFICATION

Forget the expense, clutter and hassle of an external A/V receiver. The R-51PM monitors incorporate individual ultra-low noise amplifiers custom designed to maximize system performance and eliminate the need for external amplification.

FULL FEATURED IR REMOTE

Allows easy access to system features like dedicated source selection, track controls, and play/pause.

SYSTEM EXPANDABILITY

Add a subwoofer to enhance for even more bass.

Key Features:

Simple set up	Bluetooth® wireless technology	Integrated
	Ultra low noise amplifiers	Full fe
	Digital optical, analog RCA and USB inputs	120W
	1" aluminium diaphragm compression driver	90° x
	5.25" copper spun magnetically shielded IMG woofer	Sold a

System Description:	Powered Monitor (pair)
Frequency Response:	68Hz - 21kHz
Dynamic Bass Extension:	49Hz @ 35% Volume
Max Output:	107.3 dB
Total System Power:	120W Total System Power (140W Peak) 60W per channel cont. @ <%1 THD
High Frequency Driver:	1" (2.5cm) Aluminium diaphragm compression driver mated to 90° x 90° s Tractrix® horn
Low Frequency Driver:	5.25" (13.3cm) copper spun magnetically shielded IMG woofer
Crossover Frequency:	1663 Hz (Passive)

Enclosure Material:	MDF
Enclosure Type:	Bass-reflex via rear-firing port
Inputs:	Bluetooth® wireless technology Phono/Line analog (with switch and ground screw terminal) 3.5mm analog mini jack USB digital Optical digital
Outputs:	Single RCA line level output for connection to subwoofer
Dimensions (H x W x D) :	24.8 x 14.9 x 19.1cm
Weight:	10.6kg
Finish:	Black
Voltage:	100V-240V 50/60Hz internal power supply with region specific power cords
Accessories:	Remote control (with 2 x AAA batteries) 4M speaker wire with soldered tips 2M power cord (region specific) 2M USB Type A to Type B cable Rubber Feet