

KLIPSCH R-610F BLK/GNM

Šifra: 12825
Kategorija proizvoda: Podnostojeći Zvučnici
Proizvođač: Klipsch

Cena: 33.480,00 rsd

KLIPSCH R-610F BLK/GNM

The

Klipsch Reference Base line of loudspeakers feature premium technical and industrial design characteristics, inspired by more expensive Klipsch Reference speaker designs, but at a price that belies the sound they deliver. Tuned to work both for Hi-Fi and Home Cinema applications, Klipsch Reference Base speakers rock the house like nothing else thanks to some clever technology.

Like all Klipsch speakers, the 2018 Reference range

makes use of horn technology to deliver an un-paralleled sound performance. Horn-loading allows for controlled directivity, ensuring the high-frequency energy is aimed at the listener for increased focus, dynamics, clarity and detail. Horn technology also facilitates high efficiency driver operation with low-distortion, as less electrical power is required to make a louder sound. There is also Wider Dynamic Range, which makes dialogue and vocals much clearer - distinguishing clearly between the loudest and quietest sections of a performance. However, even though there is all this increased performance, the delivery is tuned with a flat frequency response, so the audio track remains exactly as the creator intended. Cosmetically the 2018 Reference range also makes a great leap forward, compared to previous designs. There's a new, classicly-styled cabinet made from scratch-resistant black wood grain vinyl, with a thin border edge around the front baffle. The horn structure features a neat "Klipsch Reference" logo, while the IMG spun-copper woofers have injection-moulded trim rings and exposed fasteners for a stylish industrial appeal. The floorstanders also have high-strength injection-moulded feet that angle the speaker back 2° for a look reminiscent of the latest RF-7 III speakers, and all models (excl. subwoofers) feature new magnetic speaker grilles.

90° x 90° TRACTRIX HORN

Klipsch's exclusive Tractrix® horn technology delivers the power, detail and emotion of the live music experience with the cleanest, most natural sound possible.

LINEAR TRAVEL SUSPENSION (LTS) ALUMINIUM TWEETER WITH KAPTON SUSPENSION

The exclusive Linear Travel Suspension (LTS) minimizes distortion for enhanced, detailed performances. Kapton® is an extremely light and rigid material used in the tweeter suspension to provide high efficiency and improve resolution and detail. LTS tweeters are a hallmark of Klipsch speakers, making it a core component of some of the best speakers in the world.

SPUN COPPER IMG WOOFER

Injection Molded Graphite (IMG) woofer cones are exceptionally light while being extremely rigid - providing remarkable low frequency response, with minimal cone breakup and distortion. When paired with the Tractrix Horn-loaded LTS tweeter, it provides speaker efficiency highest in its class.

SLIM DESIGN

Compliments today's flat panel TVs with an unobtrusive low profile design.

TAPERED CROSSOVER

Tapered array crossovers improve dispersion resulting in improved midrange definition - critical for dialog rich material in centre channels.

SLEEK, CONTEMPORARY APPEARANCE

Exposed fasteners, angled feet and low profile magnetic grilles give the speakers a polished, modern appearance.

MDF CABINET WITH SCRATCH-RESISTANT, TEXTURED WOOD GRAIN VINYL

Stylish aesthetic with absolute durability that results in a seamless integration into any décor.

HIGH QUALITY CABINET DESIGN

Reinforced MDF construction reduces cabinet vibration for less audible colouration and improved sonic accuracy.

Key Features:

6.5” spun copper IMG woofer	Bass-Reflex via rear-firing Tractrix® ports
Scratch-resistant, textured wood grain vinyl	1” Aluminium LTS tweeter with Kapton suspension
Improved midrange definition	Stylish aesthetic
90º x 90º Tractrix Horn	Single Gold Plated Binding Posts
Injection molded feet	Sold as pair

Frequency Response:	45Hz - 21kHz +/-3dB
Sensitivity:	94 dB @ 2.83V/1M
Power Handling (Cont/Peak):	85W/340W
Nominal Impedance:	8 Ω Compatible
Crossover Frequency:	1,800Hz
High Frequency Driver:	1” Aluminium LTS tweeter mated to a 90 x 90 square Tractrix® Horn
Low Frequency Driver:	Single 6.5” spun-copper IMG woofer
Enclosure Material:	MDF
Enclosure Type:	Bass-Reflex via rear-firing Tractrix® ports
Inputs:	Single Gold Plated Binding Posts
Dimensions (H x W x D):	940 x 240 x 384mm
Weight:	16.3 kg
Finishes:	Black Textured Wood Grain Vinyl
Accessories:	Injection molded feet & screws