

# KLIPSCH R-620F Black/Gun-Metal Podnostojeći Zvučnik

Šifra: 12828  
Kategorija proizvoda: Podnostojeći Zvučnici  
Proizvođač: Klipsch

Cena: 35.880,00   rsd

Klipsch exclusive Linear Travel Suspension (LTS) aluminum tweeter minimizes distortion for enhanced, detailed performances. Using Kapton®, an extremely light and rigid material, in the tweeter suspension provides high efficiency and improve resolution and detail. LTS tweeters are a hallmark of Klipsch speakers, making them some of the best speakers in the world.

## SPUN COPPER IMG WOOFERS

Injection Molded Graphite (IMG) woofer cones are exceptionally light while being extremely rigid – providing remarkable low frequency response, with minimal cone breakup and distortion. When paired with the Tractrix Horn-Loaded LTS Tweeter, it provides speaker efficiency highest in its class.

## REAR TRACTRIX® PORT

The rear Tractrix port is perfectly matched to the cabinet and woofers, creating ideal airflow with minimal distortion or turbulence even at the lowest frequencies.

## SLEEK DESIGN

Exposed fasteners, angled feet, low profile magnetic grilles and a scratch-resistant, textured wood grain vinyl give the R-620F floorstanding speaker a polished, modern appearance.

## HIGH QUALITY CABINET DESIGN

Reinforced MDF construction reduces cabinet vibration for less audible coloration and improved sonic accuracy - giving you the ultimate listening experience that's built to last.

KLIPSCH R-620F Black/Gun-Metal Podnostojeći Zvučnik

## TRACTRIX® HORN TECHNOLOGY

Klipsch exclusive 90x90° Tractrix® horn technology ensures that the R-620F high frequency energy is aimed at the listener and reduces artificial reverb or filtering caused by indirect sound bouncing off of walls. Using this proprietary focused technology gives you the best clarity, dynamics, and detail from your movies and music.

## LINEAR TRAVEL SUSPENSION TWEETER WITH KAPTON® SUSPENSION

Frequency Response:	38Hz - 21kHz +/-3dB
Sensitivity:	96 dB @ 2.83V/1M
Power Handling (Cont/Peak):	100W/400W
Nominal Impedance:	8Ω Compatible
Crossover Frequency:	2,000 Hz
High Frequency Driver:	1" Aluminium LTS tweeter mated to a 90 x 90 square Tractrix® Horn
Low Frequency Driver:	Dual 6.5" spun-copper IMG woofers
Enclosure Material:	MDF
Enclosure Type:	Bass-Reflex via rear-firing Tractrix® ports
Inputs:	Single Gold Plated Binding Posts
Dimensions (H x W x D):	1017 x 240 x 386mm
Weight:	18.6kg

<b>Finishes:</b>	Black Textured Wood Grain Vinyl
<b>Included Accessories:</b>	Injection molded feet & screws