logo not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

KLJPSGHrRMX-42/Zvujčnich za policu

## KLIPSCH RVX 42 Zvučnici za policu

Šifra: 3572

Kategorija prozivoda: Bookshelf Zvučnici

Proizvođač: Klipsch

Cena: 35.880,00 rsd

RVX-42 Flat Panel Speaker (BLACK)

Dual 4-inch Cerametallic™ woofers 1-inch titanium-dome compression drivers Round Tractrix® Horn for maximum clarity and efficiency

Despite its slim appearance, the RVX-42 delivers an adrenaline rush of sound that's set to stun. In fact, it received a 2004 Distributed Audio Award from Electronic House Expo for being the best on-wall speaker for less than \$1,000 per pair.

With similar flatness and styling to popular plasma and LCD televisions, the Klipsch Reference Series RVX-42 is a high-performance audio solution that complements this growing consumer electronics segment.

This on-wall model has a single-piece aluminum extrusion enclosure. It employs dual 4-inch Cerametallic™ woofers and uses a 1-inch titanium-dome compression driver mated to a round Tractrix® Horn for maximum clarity and efficiency.

The RVX-42 goes well with 42-inch or larger plasma and LCD screens. It also features keyhole mounts (sized for a single-gang electrical box), two 3/8"-16 threaded inserts for optional wall mounts and a pedestal base. There are two insert locations on the RVX-42 where the pedestal can be positioned - one in the center and one on the bottom so the loudspeaker can either serve as a center channel or bookshelf. Another key feature is a bass compensation switch for the best possible sonic performance either on-wall or off-wall.

While no longer in production, the RVX-42 is still owned and listened to by Klipsch fans around the world. To connect with other people who are passionate about audio and interested in Klipsch products, visit our open forum bulletin board.

## **Specifications**

FREQUENCY RESPONSE 92-20kHz(+-)3dB POWER HANDLING 75 w max continuous (300 w peak) SENSITIVITY 94dB @ 2.83 volts / 1m

NOMINAL IMPEDANCE 8 ohms compatible

CROSSOVER FREQUENCY 2175Hz

TWEETER 1" (2.5cm) Titanium dome compression driver

HIGH FREQUENCY HORN Integral round 90(o) Tractrix(r) Horn

WOOFER Two 4" (10.2cm) Cerametallic(tm) cone, magnetically shielded

ENCLOSURE MATERIAL Extruded aluminum, ABS baffle

ENCLOSURE TYPE Bass reflex via dual side-firing ports

INPUT CONNECTIONS One set of binding post speaker terminals

DIMENSIONS 24" (61cm) H x 5.75" (14.6cm) W x 4.5" (11.4cm) D (vertical without pedestal base)

MOUNTING Pedestal base for horizontal or vertical use / three keyholes / two 3/8"-16 threaded inserts

WEIGHT 14 lbs. (6.4kg)

FEATURES Bass compensation switch for on-wall / off-wall placement FINISHES Black **BUILT FROM 2004**