

## ZOOM L-20 LiveTrak - Digitalna mikseta i snimač

Šifra: 13177  
Kategorija proizvoda: Miksete bez Snage  
Proizvođač: ZOOM



**Cena: 113.880,00 rsd**

### 20 Inputs for Bigger Sound

The LiveTrak L-20 is designed to mix bigger. It features 20 inputs (16 mono mic/line inputs and two stereo inputs), all with independent 3-band mid-parametric EQ. The 16 mono inputs offer stand-alone compressor control.

### 22 Tracks of Recording

Record 20 discrete channels plus a stereo mix directly to an SD card. The LiveTrak L-20 captures pristine audio in resolutions up to 24-bit/96 kHz.\* At -128 dBu EIN with +60 dB maximum input gain, the L-20 is equipped with our quietest and most advanced preamps ever. Mix down finished songs on the L-20 or transfer your discrete tracks to a DAW to perfect later.

\*Effects, EQ, overdub, audio interface, and fader modes A-F are not available in 96 kHz.

### Create Six Custom Monitor Mixes

With six independent monitor outputs for musicians, each output can have its own custom mix, complete with effects, that can easily be switched from a powerful headphone output, to a balanced line output for stage monitors.

### And One for the House

The LiveTrak L-20 features a dedicated 7th output for the FOH engineer. The sound engineer can monitor the main mix and any of the sub mixes, thus adjusting them to the musicians' satisfaction.

### Channel Strip

All 20 inputs include a channel fader as well as dedicated mute and solo buttons. The 16 mono inputs include single-knob compression and gain control. Record or playback individual channels with the "Rec/Play" button.

### EQ Control

The L-20 provides a smooth 3-band mid-parametric EQ and a variable frequency low-cut for each channel. Use the "Select" button to apply Channel Strip settings to the selected channel.

### 2 EFX Sends

The L-20 offers 20 built-in effects with adjustable parameters. Choose from delay and reverb effects, then apply them to any channel using two dedicated EFX busses.

### Broad Connectivity

The L-20's combo inputs support XLR or ¼-inch connections. Channels 1-2 offer Hi-Z inputs for electric

guitar or bass. Channels 17/18 and 19/20 have TS line connectivity for keyboards and other audio devices, as well as RCA inputs.

#### Navigation and Display

The LiveTrak L-20's bright, backlit LCD screen and encoder knob let you access an intuitive menu to create new projects, recall previous projects, and customize your recorder settings.

#### Slate Mic and Metronome

Use the built-in slate mic to record comments or talk-back. Push the tempo button to program the metronome to your desired tempo.

#### Transport Controls and Overdub Button

Transport controls include Record, Play/Pause, Stop, Fast Forward, and Rewind. The overdub button allows you to record additional tracks to your current project.

#### Six Custom Monitor Mixes

The "Fader Mode" buttons allow you to design custom mixes for both the master and monitor outs. For each output, easily switch between a powerful headphone output and a balanced line output for stage monitors.

#### Headphone Output for FOH

The L-20 includes a dedicated headphone output for front-of-house, enabling them to monitor any of the custom sub mixes as well as the master mix.

#### Custom Scene Settings

Create and save up to nine different scenes to recall fader position, EQ settings, pan, mute, and more.

#### Big Beautiful Interface

Although the LiveTrak L-20 is designed to work as a stand-alone recording and mixing console, it can also be used as a 22-in/4-out USB audio interface. Audio Interface mode lets you route inputs to any DAW or streaming software, even while recording to an SD card. Additionally, audio can be routed from your computer into the L-20 to be mixed with your live performance. Class compliant mode, which enables connection with iOS devices, is supported as well.\*

\*Apple Lightning to USB Camera Adapter required.

#### Wireless Mixing

The LiveTrak L-20 offers wireless control\* via a free iOS mobile app "L-20 Control" featuring most onboard functions, including Fader Levels and Modes, Scenes, EQ, EFX sends, returns, parameters, and more. You can even manage your Effects Library and Scene Library right from your device. Control it all on either large Monitor Out view with a mini transport, or a mini Monitor Out view with expanded Transport controls.

\* Zoom Bluetooth adapter (ex. BTA-1) required. Communication at up to 10 meters is possible in an unobstructed indoor space with BTA-1 units.

#### LiveTrak L-20 Features

20 discrete channels (16 mono plus 2 stereo) with XLR or ¼-inch connectivity

22-track simultaneous recording, 20-track playback

22-in/4-out USB audio interface connectivity

Records up to 24bit/96kHz audio to SD card

48V phantom power

Hi-Z connectivity (channels 1-2)

26dB pad (channels 3-16)

Built-in compression control (Channels 1-16)

Solo buttons for individual channels

Variable frequency low-cut control

Main outputs plus 6 customizable monitor outputs

Dedicated headphone output for sound engineer

Scene saving function, up to 9 scenes saved at a time

20 built-in chorus, delay and reverb effects with adjustable parameters

Two effect busses  
Built-in slate mic  
Class-compliant mode (for iOS compatibility)  
Compatible with Remote Mixer app for iPad  
Automatic recording starting/stopping capability  
Pre-record function  
Import/export projects with USB 2.0 host port  
Compatible functions for ZOOM FS01 footswitch  
Automatic power-save function

#### What's in the Box

Included with the L-20

LiveTrak L-20

AD-19 AC Adapter

USB 2.0 Cable

Quick Guide

#### Optional Accessories

RKL-12 Rack Mount Adapter

BTA-1 Bluetooth Adapter

FS01 Momentary Footswitch

CBL-20 Carrying Bag