Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615 PIB: 106966344 E-mail: porudzbine@player.rs

M-AUDIOOMJRAGK PIKUSVH

All Are

M-AUDIO M TRACK PLUS II

Šifra: 10529 Kategorija prozivoda: USB Zvučne kartice Proizvođač: M-AUDIO

Cena: 19.080,00 rsd

M-Track Plus is equipped with versatile inputs to provide the best results with any type of audio source. Each channel offers a combination XLR and balanced 1/4" input. The XLR input is designed to work with microphones or other Lo-Z sources. The phantom power switch delivers 48V to the XLR inputs for use with professional condenser microphones. The 1/4" input can be set to receive line level signal, or switched to allow an electric

guitar, bass or any other instrument level source to be plugged directly into the M-Track Plus, while the gain knob ensures the proper input level.

Welcome

Improved Inline Monitoring M-Track Plus offers zero-latency

M-Track Plus offers zero-latency monitoring of the input signal through both the main and headphone outputs. The monitor mix knob adjusts the balance between the direct inputs and the playback from your computer software. This makes it easy to record new parts or add parts to an existing composition. The Headphone output offers its own level control.

LED Metering

Multi-color LED metering provides instant visual feedback of the input levels.

Studio Software Inside

Ableton Live Lite delivers much of the functionality of Ableton Live—the revolutionary, multi-award winning music production solution that allows you to spontaneously compose, record, remix, improvise and edit your musical ideas in a seamless audio/MIDI environment. Live brings your acoustic, electronic and virtual instruments—as well as your digital audio recordings and MIDI sequences—together in a single interface with unparalleled ease of use.

Building on the same core technologies found in Steinberg's popular Cubase, Cubase LE is a special compact version offering all the basic tools for recording, editing and mixing everything from the basic idea to the final masterpiece. Included are over 18 effects, time stretching and pitch shifting, plus convenient project templates to assist with various production tasks. Cubase LE offers powerful yet easy-to-use software tools for a large range of music styles

Professional Sound With Waves

The M-Track Plus software suite also includes an impressive selection of plugin effects from Waves Audio Ltd. TrueVerb delivers a broad, natural reverb with an easy-to-use interface. AudioTrack offers a remarkable EQ, plus gating and compression. Plus, you can add a professional touch with the Eddie Kramer Effects Channel, created with legendary audio guru Eddie Kramer.

Specifications

All specifications are measured at 20 kHz bandwidth. Specifications are subject to change without notice Mic Inputs 1-2 (balanced XLR) Frequency Response: 20 Hz - 20 kHz (+/-0.1 dB) Dynamic Range: 104 dB (A-weighted) Signal-to-Noise Ratio: 104 dB (1 kHz, +1.4 dBu, A-weighted) THD+N: 0.003% (1 kHz, +2 dBu input, -0.8 dBFS) Preamp EIN: -133 dBu (max gain, weighted) -126 dBu (max gain, 150 Ω source, unweighted) Sensitivity: -53 dBu Gain Range: 55 dB

Inst Input 1 and 2 (unbalanced 1/4" [6.35 mm] TS)

Frequency Response: 20 Hz - 20 kHz (+/-0.1 dB) THD+N: 0.022% (1 kHz, -1 dBFS) Sensitivity: -47 dBu Input Impedance: 1 MΩ Gain Range: 55 dB

Power: USB bus-powered

Weight: 2.29 lbs (1.04 kg)

Features

M-Track Plus (MKII) Pro-grade audio recording with up to 24bit/96 kHz resolution Solid metal chassis and low profile design **Dedicated Channel** Line/Instrument controls for receiving line-level signals and plugging in instruments directly (2) XLR+1/4" combo inputs with phantom power for recording vocals, guitars, bass, and more Channel-specific LED VU meters provide real-time visual feedback of the audio signal Zero-latency monitoring with USB/Analog Direct Balance control (2) Balanced 1/4" main outputs with dedicated level control Headphone out with independent level control for private recording and

mixing USB-powered connectivity and solid metal construction for on-the-go use Line Inputs 1-2 (balanced 1/4" [6.35 mm] TRS) Frequency Response: 20 Hz - 20 kHz (+/-0.1 dB) THD+N: 0.022% (1 kHz, -1 dBFS) Sensitivity: -43dBu Gain Range: 55 dB

Main Outputs, L and R (impedance-balanced 1/4" [6.35 mm] TRS) Frequency Response: 20 Hz - 20 kHz (+/-0.3 dB) Dynamic Range / Signalto-Noise Ratio: 102 dB (A-weighted) THD+N: 0.008% (1 kHz, -1 dBFS) Max Output Level: +2.86 dBu

Size (H x W x D): 2.07 x 9.4 x 4.85 inches (52.58 x 238.76 x 123.19 mm)