Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Martin Wisman MA 2600 - Razglasno pojačalo



Šifra: 05090
Kategorija prozivoda: Razglasna Pojačala
Proizvođač: Martin Wisman

Cena: 81.708,00 rsd

MA 2600

Power Amplifier

The MA Series professional power amplifiers offer Martin Wisman renowned integrity and can handle exceptionally high power ratings in a compact, light weight 2RU package. The α Series amps also feature Automatic Clip Limiting to protect connected drivers;Impedance sensing to accommodate varying impedance outputs; tunnel cooled,high efficiency heat sinks; and variable speed DC fans to limit the operating temperature and extend amplifier life. Models in the series include the MA 2600 and MA 3200.

Minimum Guaranteed Power

1 kHz with 0.5% THD

Stereo, 4 ohms (per ch.)	1280W
Stereo, 8 ohms (per ch.)	800W
Bridge mono, 8 ohms	2400W

Performance

Sensitivity (volts RMS) for full rated power at 8 ohms	0.775V, 32dB, 26dB
Frequency Response (at 1 watt, 20Hz - 25 kHz)	+0dB, -0.5dB
Phase Response (at 1 watt , 20Hz to 20 kHz)	+10°,-20°

Signal to Noise Ratio below rated power A-weighted	
Total Harmonic Distortion (THD) at 1 full bandwidth power, from 20 Hz to 20 kHz	
Intermodulation Distortion (IMD) 60 Hz and 7 kHz at 4:1, from full rated output to -35 dBt	
Damping Factor (8 ohm): 20 Hz to 400 Hz	
Low Cut:Linkwitz-Riley (24dB/Octave)	Off/35Hz/80Hz
L**ow Pass**:Linkwitz-Riley (24dB/Octave)	Off/80Hz/125Hz
Crosstalk (below rated power, 20 Hz to 20 kHz)	
Common Mode Rejection (CMR)(20 Hz to 1 kHz)	
DC Output Offset (Shorted input)	
Input Impedance (nominally balanced, nominally unbalanced)	20 kilohms, 10 kilohms
Voltage Gain (at maximum level setting)	40.3dB gain at 0.775volt sensitivity
Load Impedance (Note: Safe with all types of loads)	Stereo Bridge 4-8 ohms
	Mono 8 ohms
AC Line Voltage and Frequency Configurations Available (±10%)	~220-240 V and 50/60 Hz
AC Line Current (both amplifiers draw no more than 90 watts at idle)	12A

Construction

Ventilation	Flow-through ventilation from front to back
Cooling	Proportional speed fan
Dimensions	H × W × D: 89mm×483mm×462mm
Net Weight	18kg

Shipping Weight	21kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.