

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

MARTIN AUDIO Blackline F10+ - Pasivni zvučnik

MARTIN AUDIO Blackline F10+ - Pasivni zvučnik

Šifra: 10437
Kategorija prozivoda: Pasivne Zvučne Kutije
Proizvođač: Martin Audio

Cena: **151.680,00** rsd

It features a powerful 10" (250mm) low frequency driver and a 1" (25mm) HF compression driver mounted on a constant directivity 90° x 50° horn. Depending on the application, the HF horn can be rotated to allow the multi-angle enclosure to be used in either its vertical or horizontal orientation. A demodulating ring fitted to the LF driver reduces distortion and improves the performance at the upper end of the LF driver's range at high levels. Additionally, the directivity of the LF driver has been matched to the HF horn by a combination of optimisation of the water-resistant LF cone profile and improved crossover design. Use of a controller with the F10+ is optional. For demanding applications, an M3+ or DX1.5 controller configured to perform EQ and limiter functions is recommended.

Compact two-way system

User rotatable 90° x 50° horn
Five year limited warranty

Flexibility

TYPE	Compact, two-way passive
FREQUENCY RESPONSE (5)	65Hz-20kHz ± 3dB -10dB @ 56Hz
DRIVERS	10" (250mm)/2.5" (63.5mm) voice coil LF driver 1" (25mm) exit HF compression driver
RATED POWER (2)	300W AES, 1200W peak
RECOMMENDED AMPLIFIER	MA2.0
SENSITIVITY (6)	96dB
MAXIMUM SPL (9)	121dB continuous, 127dB peak
NOMINAL IMPEDANCE	8 ohms
DISPERSION (-6dB)	90° horizontal, 50° vertical
CROSSOVER	2.5 kHz passive
ENCLOSURE	27.7 litre, multi-laminate birch ply
FINISH	Textured black paint
PROTECTIVE GRILLE	Black perforated steel
CONNECTORS	2 x Neutrik NL4
PIN CONNECTIONS	FR+,- : 1+,1-, Link thro': 2+,2-

FITTINGS	10 x M8, 4 x M8 threaded inserts 1 x mounting pole socket 1 x pocket handle
DIMENSIONS	(W) 351mm x (H) 500mm x (D) 317mm (W) 13.8ins x (H) 19.7ins x (D) 12.5ins
WEIGHT	17kg (37lbs)