Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

# MARTIN AUDIO BLACKLINE X210SUB - Pasivni vufer



Šifra: 12368
Kategorija prozivoda: Pasivni Subwooferi
Proizvođač: Martin Audio

## Cena: 129.492,00 rsd

Martin Audio Blackline X210
The loudspeaker shall be a slimline subwoofer consisting of two 10” reflex-loaded, long-excursion, low frequency transducers.
The on-axis frequency response shall be 50Hz-150kHz +/- 3dB and the loudspeaker shall produce a maximum SPL of 133dB peak calculated at 1 metre. Power handling shall be 500W AES, 2000W peak. Rated impedance shall be 4 ohms. The rear connector panel shall be fitted with two NL4 type connectors and the loudspeaker shall be operated in conjunction with a dedicated electronic controller. The enclosure shall be made from plywood and finished with a black textured paint. Optional white and RAL colour finishes shall be available to special order. The enclosure shall be fitted with M8 threaded inserts for eyebolt suspension and the drivers shall be protected by a perforated steel grille. Dimensions (W x H x D) including feet shall be 720mm x 295mm x 465mm (28.3in x 11.6in x 18.3in). Weight shall be 20kg (44.1lbs).
The loudspeaker shall be the Martin Audio X210.
Features
Slimline direct-radiator subwoofer
2 x 10” (250mm) drivers with 2” (50mm) voice coils
Large ports for reduced air noise
Perforated steel grille
4Ω nominal impedance
M10 flying inserts
Applications
Portable sound reinforcement
Live music clubs
Bars and restaurants
Nightclubs
Corporate AV events and conferences
Weddings and parties
Secondary stages at festivals
HoW, leisure centres and retail outlets

| | |
|---|---|
| TYPE | Slimline, direct radiating subwoofer |
| FREQUENCY RESPONSE (5) | 50Hz-150Hz ± 3dB, -10dB @ 42Hz |
| DRIVER | 2 x 10” (250mm)/2” (50mm) voice coil, long excursion, ferrite magnet |
| RATED POWER (2) | 500W AES, 2000W peak |
| SENSITIVITY (8) | 103dB |

| | |
|---|---|
| MAXIMUM SPL (9) | 127dB continuous, 133dB peak (half space) |
| NOMINAL IMPEDANCE | 4Ω |
| DISPERSION (-6DB) | Omnidirectional |
| CROSSOVER | 80-120Hz active |
| ENCLOSURE | Birch/poplar ply |
| FINISH | Black textured paint |
| PROTECTIVE GRILLE | Black perforated steel |
| CONNECTORS | 2 x NL4 type |
| PIN CONNECTIONS (INPUT) | 1+/1- |
| PIN CONNECTIONS (LINK) | 1+/- to 1+/- |
| FITTINGS | 16 x M8 inserts, 2 x bar handles |
| DIMENSIONS | (W) 720mm x (H) 295mm x (D) 465mm<br>(W) 28.3ins x (H) 11.6ins x (D) 18.3ins |
| WEIGHT | 20kg (44.1lbs) |

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.