

MARTIN AUDIO BLACKLINE X8 - Pasivni zvučnik

MARTIN AUDIO BLACKLINE X8 - Pasivni zvučnik

Šifra: 13104
Kategorija prozivoda: Pasivne Zvučne Kutije
Proizvođač: Martin Audio

Cena: 62.280,00 rsd

Martin Audio Blackline X8

The loudspeaker shall be a passive, two-way system. Its transducers shall consist of a reflex-loaded 8" low frequency driver and a 1" diaphragm/1" exit compression driver mounted on a high frequency horn which shall be user-rotatable to enable vertical or horizontal orientation of the enclosure.

Horizontal dispersion shall be 90° and vertical dispersion shall be 50°. The on-axis frequency response shall be 70Hz-20kHz +/- 3dB and the loudspeaker shall produce a maximum SPL of 121dB peak calculated at 1 metre. Power handling shall be 200W AES, 800W peak. Rated impedance shall be 8 ohms.

The rear connector panel shall be fitted with two NL4 type connectors. Low and high frequency sections shall be integrated by an internal 2.9kHz passive network. For optimal performance the loudspeaker shall be operated in conjunction with a dedicated electronic controller.

The symmetrical, multi-angle enclosure shall be made from plywood and finished with a black textured paint. Optional white and RAL colour finishes shall be available to special order. The enclosure shall be fitted with a pole-mount socket and M8 threaded inserts to accommodate eyebolt suspension and a wall bracket. The drivers shall be protected by a perforated steel grille with scrim cloth backing.

Dimensions (W x H x D) shall be 257mm x 422mm x 243mm (10.1in x 16.6in x 9.6in). Weight shall be 8kg (17.6lbs).

The loudspeaker shall be the Martin Audio Blackline X8.

Features

Ultra-Compact passive two-way system	Symmetrical multi-angle plywood enclosure	User-n
	Vertical and horizontal orientation	Screw
	Integral ergonomic handle	Pole-m
	8Ω nominal impedance	Twin M
	Flexible mounting options via M8 inserts	

PIN CONNECTIONS (LINK)
FITTINGS
DIMENSIONS
WEIGHT
ACCESSORIES