

MARTIN AUDIO C6.8T - Plafonski zvučnik

Šifra: 12647
Kategorija proizvoda: Plafonski Zvučnici
Proizvođač: Martin Audio

Cena: 25.080,00 rsd

Very wide dispersion – 150° conical up to 7kHz
High & low impedance operation – transformer included
106dB continuous max SPL @ 1 metre
75W power handling – 16 ohm (40W transformer)
Polyswitch and thermal fuse protection
Steel backcan
UL2043 & UL1480

Applications

Fixed installations in ceiling and walls
Low ceiling environments

The side-by-side arrangement of the drive units maintains smooth response up to 75° off-axis and makes the C6.8T perfectly suited for use in low ceilings, where its broad coverage means that fewer units will be required to deliver premium sound over the required listening area. The C6.8T features a 4-point mounting system for ease of installation and a rising clamp plug and socket permit easy pre-wiring with up to 2.5mm² conductors.

These products comply with UL2043 Fire Tests for Heat & Visible Smoke Release for Discrete Products and their Accessories Installed in Air Handling Spaces.

Listed UL1480 General Signalling Speakers.

SUITABLE FOR USE IN AIR HANDLING SPACES

MARTIN AUDIO C6.8T - Plafonski zvučnik

Featuring a 6.5" (165mm) bass driver and a 0.8" (19mm) dome tweeter, The C6.8T is ideal for flush mounted applications where full frequency performance and wide dispersion are required from a compact, ported enclosure.
Features

Two-way high performance flush mounting ceiling speaker
6.5" (165mm) UL94V-0 carbon fibre loaded polypropylene cone bass driver

TYPE	Ceiling mounted, two-way vented enclosure
FREQUENCY RESPONSE (5)	90Hz-20kHz ± 3dB -10dB @ 70Hz

DRIVER	6.5" (165mm) UL94V-0 PP bass driver 0.8" (19mm) dome tweeter
RATED POWER (2)	75W AES, 300W peak
SENSITIVITY (8)	89dB
MAXIMUM SPL (9)	106dB continuous, 112dB peak
NOMINAL IMPEDANCE	16Ω
DISPERSION (-6dB)	150° conical up to 7kHz
CROSSOVER	4kHz passive
ENCLOSURE	Steel backcan
FINISH	Bezel & grille – white UV resistant (Overpaintable) Backcan – zinc plated
PROTECTIVE GRILLE	Perforated steel
CONNECTORS	Rising clamp plug and socket
ACCESSORIES (included)	40W 70/100V line transformer Tile rails C bracket Paint mask Cut-out template
VOLTAGE TAPS	100V – 40W, 20W, 10W 70V – 40W, 20W, 10W, 5W
DIMENSIONS	(OD) 260mm x (D) 181mm (OD) 10.2ins x (D) 7.1ins
CUT-OUT DIAMETER	224mm (8.83 ins)
WEIGHT	3.5kg (7.7lbs)

