not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

MARTIN AUDIO CDD5W - Nazidni zvučnik

Šifra: 13067

Kategorija prozivoda: Nazidni Zvučnici

Proizvođač: Martin Audio

Cena: 35.880,00 rsd

MARTIN AUDIO (GDD5Wow/Nazidni zvučnik

Martin Audio

CDD5

The loudspeaker shall be a passive, two-way system ultilising Coaxial Differential Dispersion technology. Its transducers shall consist of a reflex-loaded 5.25" low frequency driver and a coaxially-mounted 0.75" dome high frequency driver loaded by a static waveguide that merges with moving waveguides added to the cone of the low frequency driver to define the HF horn geometry.

The coaxial driver shall be user-rotatable to enable vertical or horizontal operation as required by the

application. Horizontal dispersion shall vary from 120° to 90° and vertical dispersion shall be 80°. The onaxis frequency response shall be 100Hz-20kHz +/- 3dB and the loudspeaker shall produce a maximum SPL of 116dB peak calculated at 1 metre. Power handling shall be 100W AES, 400W peak. Rated impedance shall be 8 ohms.

The input connector shall be a low-profile 13A push-lock type. Low and high frequency sections shall be integrated by an internal 2.5kHz passive network. For optimal performance the loudspeaker shall be operated in conjunction with a dedicated electronic controller.

The enclosure shall be made from ABS material and fitted with threaded inserts for wall and ceiling mounting. The drivers shall be protected by a perforated steel grille with scrim cloth backing. Dimensions (W \times H \times D) shall be 160mm \times 230mm \times 149mm (6.3in \times 9.1in \times 5.9in). Weight shall be 2.7kg (6lbs).

The loudspeaker shall be the Martin Audio CDD5.

Features

Ultra-Compact, CDD $^{\text{\tiny M}}$ passive two-way system Elegant ABS moulded enclosure Vertical and horizontal mounting options 8Ω nominal impedance Black or white standard colour options

Coaxial Differential Dispersion™ technology User-rotatable coaxial drive unit Screw-free perforated steel grille Discreet mounting accessories 70V/100V line transformer option

PIN CONNECTIONS	Left to right: Input+, Input-, Link +
FITTINGS	6 x M5 inserts for wall/ceiling brackets
DIMENSIONS	(W) 160mm x (H) 230mm x (D) 149mm (W) 6.3ins x (H) 9.1 ins x (D) 5.9 ins
WEIGHT	3kg (6.6lbs)