**logo**e not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

Fax: +381 11 3347 PIB: 106966344

E-mail: porudzbine@player.rs

## MARTIN AUDIO CDD8B - Nazidni zvučnik

Šifra: 13107

Kategorija prozivoda: Nazidni Zvučnici

Proizvođač: Martin Audio

Cena: 71.880,00 rsd

## MARTIN AUDIO (QDD8BowrNazidni zvučnik

## Martin Audio CDD8

The loudspeaker shall be a passive, two-way system ultilising Coaxial Differential Dispersion technology. Its transducers shall consist of a reflex-loaded 8" low frequency driver and a coaxially-mounted 1" exit high frequency compression driver loaded by a static waveguide that merges with moving waveguides added to the cone of the low frequency driver to define the HF horn geometry.

The coaxial driver shall be user-rotatable to enable vertical or horizontal operation as required by the

application. Horizontal dispersion shall vary from  $110^\circ$  to  $80^\circ$  and vertical dispersion shall be  $60^\circ$ . The on-axis frequency response shall be 70Hz-20kHz +/- 3dB and the loudspeaker shall produce a maximum SPL of 123dB peak calculated at 1 metre. Power handling shall be 200W AES, 800W peak. Rated impedance shall be 8 ohms.

The input connector shall be a low-profile 13A push-lock type. Low and high frequency sections shall be integrated by an internal 2.3kHz passive network. For optimal the loudspeaker shall be operated in conjunction with a dedicated electronic controller.

The enclosure shall be made from rigid composite material and fitted with threaded inserts for wall and ceiling mounting. The drivers shall be protected by a perforated steel grille with scrim cloth backing. Dimensions (W  $\times$  H  $\times$  D) shall be 256mm  $\times$  410mm  $\times$  252mm (10.1in  $\times$  16.1in  $\times$  9.9in). Weight shall be 9.5kg (21lbs).

The loudspeaker shall be the Martin Audio CDD8.

## **Features**

Ultra-Compact, CDD  $^{\text{\tiny M}}$  passive two-way system Elegant UPM Formi composite enclosure Vertical and horizontal mounting options  $8\Omega$  nominal impedance

Black or white standard colour options

Coaxial Differential Dispersion™ technology User-rotatable coaxial drive unit Screw-free perforated steel grille Discreet mounting accessories

CONNECTORS	Low profile 13A push-lock
PIN CONNECTIONS	Left to right: Input+, Input -, Link +
FITTINGS	6 x M6 inserts for wall/ceiling brackets
DIMENSIONS	(W) 256mm x (H) 410mm x (D) 252mm (W) 10.1ins x (H) 16.1ins x (D) 9.9ins
WEIGHT	9.5kg (21lbs)