Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

MARTIN AUDIO CDD8B - Nazidni zvučnik



Šifra: 13107
Kategorija prozivoda: Nazidni Zvučnici
Proizvođač: Martin Audio

Cena: 71.880,00 rsd

Martin Audio CDD8
The loudspeaker shall be a passive, two-way system ultilising Coaxial Differential Dispersion technology. Its transducers shall consist of a reflex-loaded 8” low frequency driver and a coaxially-mounted 1” exit high frequency compression driver loaded by a static waveguide that merges with moving waveguides added to the cone of the low frequency driver to define the HF horn geometry.
The coaxial driver shall be user-rotatable to enable vertical or horizontal operation as required by the application. Horizontal dispersion shall vary from 110° to 80° and vertical dispersion shall be 60°. The on-axis frequency response shall be 70Hz-20kHz +/- 3dB and the loudspeaker shall produce a maximum SPL of 123dB peak calculated at 1 metre. Power handling shall be 200W AES, 800W peak. Rated impedance shall be 8 ohms.
The input connector shall be a low-profile 13A push-lock type. Low and high frequency sections shall be integrated by an internal 2.3kHz passive network. For optimal the loudspeaker shall be operated in conjunction with a dedicated electronic controller.
The enclosure shall be made from rigid composite material and fitted with threaded inserts for wall and ceiling mounting. The drivers shall be protected by a perforated steel grille with scrim cloth backing. Dimensions (W x H x D) shall be 256mm x 410mm x 252mm (10.1in x 16.1in x 9.9in). Weight shall be 9.5kg (21lbs).
The loudspeaker shall be the Martin Audio CDD8.

Features

Ultra-Compact, CDD™ passive two-way system
Coaxial Differential Dispersion™ technology
Elegant UPM Formi composite enclosure
User-rotatable coaxial drive unit
Vertical and horizontal mounting options
Screw-free perforated steel grille
8Ω nominal impedance
Discreet mounting accessories
Black or white standard colour options

RATED POWER (2)	200W AES, 800W peak
SENSITIVITY (8)	94dB
MAXIMUM SPL (9)	117dB continuous, 123dB peak
NOMINAL IMPEDANCE	8Ω
DISPERSION (-6DB)	110˚-80˚ horizontal, 60˚ vertical (user-rotatable)
CROSSOVER	2.3kHz passive
ENCLOSURE	14 litre, composite material
FINISH	Black or white textured paint
PROTECTIVE GRILLE	Black or white perforated steel with scrim cloth backing
CONNECTORS	Low profile 13A push-lock
PIN CONNECTIONS	Left to right: Input+, Input -, Link -, Link +
FITTINGS	6 x M6 inserts for wall/ceiling brackets
DIMENSIONS	(W) 256mm x (H) 410mm x (D) 252mm (W) 10.1ins x (H) 16.1ins x (D) 9.9ins
WEIGHT	9.5kg (21lbs)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.