


## MARTIN RUSH MH 3 Beam B-Stock

Šifra: 8935  
 Kategorija proizvoda: Roto Glave  
 Proizvođač: Martin

**Cena: 251.880,00 rsd**

### MARTIN RUSH MH 3 Beam B-Stock



The RUSH MH 3 Beam is a powerful beam moving head that blasts an intense and narrow long-throw beam for spectacular mid-air looks and effects. It houses a fixed gobo wheel and color wheel with a multitude of effects possible from a dimmer and strobe, frost, zoom, 8-facet prism and focus.

Powerful beam moving head  
 Mid-air effects  
 Color wheel  
 Frost effect  
 Motorized focus  
 3 & 5 pin XLR

Sharp, narrow long-throw beam  
 Fixed gobo wheel  
 Mechanical dimming and strobe  
 8-facet prism  
 Battery-powered display

Length: 418 mm (16.5 in.)
Width: 321 mm (12.6 in.)
Height: 489 mm (19.3 in.)
Weight: 20.5 kg (45.2 lbs.)
Approved lamp: Philips MSD Platinum 5R
Color temperature: 8000 K
CRI (Color rendering index): 75
Average lifetime: 2000 hours
Color wheel: 14 colors plus open, rotation with variable direction and speed
Static gobo wheel: 17 gobos plus open, wheel rotation and shake
Pre-programmed effects: 31 pan and tilt macros, adjustable speed
Shutter: Strobe effect, pulse effects, instant open and blackout
Prism: 8-facet, indexing and rotation with variable direction and speed
Frost: Fade in/out
Zoom: Motorized
Focus: Motorized
Dimmer: 0 - 100%, four dimming curve options
Pan: 540°
Tilt: 270°
Pan and tilt speed: Adjustable via onboard control panel and DMX

Control: DMX

DMX channels: 19

Setting and addressing: Control panel with LCD display

DMX compliance: USITT DMX512/1990

Beam angle: 1° - 3.8°

Color: Black

Housing: High-impact flame-retardant thermoplastic

Protection rating: IP20

Mounting points: Two quarter-turn brackets for rigging clamps

Location: Indoor use only, must be fastened to surface or structure

Orientation: Any

AC power input: Neutrik PowerCon

DMX data in/out: 3-pin and 5-pin locking XLR

AC power: 100-240 V nominal, 50/60 Hz

Typical total power consumption: 390 W

*Power consumption figures are typical, not maximum. Allow for +/-10% variation.*

Cooling: Forced air (temperature-regulated, low noise)

Maximum ambient temperature (Ta max.): 40° C (104° F)

Minimum ambient temperature (Ta min.): 0° C (32° F)

Power cable, 1.5 m (4.9 ft.), without mains plug

Mounting brackets

RUSH MH 3 Beam™ in cardboard box

© 2013 Martin Professional A/S. Specifications subject to change without notice