

MARTIN RUSH Strobe 1 5x5

Šifra: 08985

Kategorija proizvoda: Strobovi

Proizvođač: Martin

Cena: 102.000,00 rsd



RUSH Strobe 1 5x5

This white strobe/blinder is a 5 x 5 LED matrix panel with individually-controllable LEDs. Controllable via multiple DMX options or sound activated, it includes preprogrammed effect, letter and number macros for easy-to-produce graphics and messaging. Panels link via an integrated horizontal and vertical locking mechanism.



White LED strobe/blinder

- 5 x 5 matrix panel
- Individually controllable LEDs
- Preprogrammed macros (effects, letters, numbers, etc.)
- Linkable - integrated horizontal and vertical locking
- DMX or sound activated
- Multiple DMX control options
- 3 & 5 pin XLR

RUSH Strobe 1 5x5 Specifications

This white strobe/blinder is a 5 x 5 LED matrix panel with individually-controllable LEDs. Controllable via multiple DMX options or sound activated, it includes preprogrammed effect, letter and number macros for easy-to-produce graphics and messaging. Panels link via an integrated horizontal and vertical locking mechanism.

Features

- White LED strobe/blinder
- 5 x 5 matrix panel
- Individually controllable LEDs
- Preprogrammed macros (effects, letters, numbers, etc.)
- Linkable - integrated horizontal and vertical locking
- DMX or sound activated
- Multiple DMX control options
- 3 & 5 pin XLR

Length: 500 mm (19.7 in.)

Width: 101 mm (4.0 in.)

Height: 500 mm (19.7 in.)

Weight: 9.5 kg (20.9 lbs.)

Strobe effect: Electronic, with regular and random pulse, burst and strobe effects

Pre-programmed effects: Effect, letter and number display macros

Electronic dimming: 0 - 100% continuous, individually dimmable pixels

Effects orientation: Standard or inverted 180°

Control options: DMX, stand-alone

DMX channels: 4/25/29

Stand-alone trigger options: Music trig, auto trig

Stand-alone sequences: 8 pre-programmed shows or random show

Stand-alone memory: 20 scenes

Setting and addressing: Control panel with LCD display

DMX compliance: USITT DMX512/1990

Light source: 25 x 5 W Cree cool white LEDs

Color temperature: 6000 - 6500 K

Minimum LED lifetime: 50 000 hours (to >70% luminous output)*

**Manufacturer's figure obtained under manufacturer's test conditions*

Color: Black

Housing: Steel

Protection rating: IP20

Location: Indoor use only, must be fastened to surface or structure

Mounting points: Integral hanging brackets (removable), side-by side mounting locks

Orientation: Any

AC power in/thru: Neutrik PowerCon

DMX data in/out: 3-pin and 5-pin locking XLR

AC power: 100-240 V nominal, 50/60 Hz

Typical total power consumption: 148 W

Power consumption figures are typical, not maximum. Allow for +/-10% variation.

Cooling: Forced air (temperature-regulated, low noise)

Maximum ambient temperature (Ta max.): 40° C (104° F)

Minimum ambient temperature (Ta min.): 0° C (32° F)

Mounting brackets incl. screws

Power cable 1.5 m (4.9 ft.)

RUSH Software Uploader 1™

Downloads

Image not found or type unknown

