Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs


MARTIN RUSH Strobe 1 5x5

Šifra: 08985
Kategorija prozivoda: Strobovi
Proizvođač: Martin



Cena: 95.880,00 rsd

RUSH Strobe 1 5x5
This white strobe/blinder is a 5 x 5 LED matrix panel with individually-controllable LEDs. Controllable via multiple DMX options or sound activated, it includes preprogrammed effect, letter and number macros for easy-to-produce graphics and messaging. Panels link via an integrated horizontal and vertical locking mechanism.



White LED strobe/blinder
5 x 5 matrix panel
Individually controllable LEDs
Preprogrammed macros (effects, letters, numbers, etc.)
Linkable - integrated horizontal and vertical locking
DMX or sound activated
Multiple DMX control options
3 & 5 pin XLR

RUSH Strobe 1 5x5 Specifications
This white strobe/blinder is a 5 x 5 LED matrix panel with individually-controllable LEDs. Controllable via multiple DMX options or sound activated, it includes preprogrammed effect, letter and number macros for easy-to-produce graphics and messaging. Panels link via an integrated horizontal and vertical locking mechanism.
Features
White LED strobe/blinder 5 x 5 matrix panel Individually controllable LEDs Preprogrammed macros (effects, letters, numbers, etc.) Linkable - integrated horizontal and vertical locking DMX or sound activated Multiple DMX control options 3 & 5 pin XLR
Length: 500 mm (19.7 in.)
Width: 101 mm (4.0 in.)
Height: 500 mm (19.7 in.)
Weight: 9.5 kg (20.9 lbs.)
Strobe effect: Electronic, with regular and random pulse, burst and strobe effects
Pre-programmed effects: Effect, letter and number display macros
Electronic dimming: 0 - 100% continuous, individually dimmable pixels
Effects orientation: Standard or inverted 180°
Control options: DMX, stand-alone
DMX channels: 4/25/29
Stand-alone trigger options: Music trig, auto trig
Stand-alone sequences: 8 pre-programmed shows or random show
Stand-alone memory: 20 scenes
Setting and addressing: Control panel with LCD display

DMX compliance: USITT DMX512/1990
Light source: 25 x 5 W Cree cool white LEDs
Color temperature: 6000 - 6500 K
Minimum LED lifetime: 50 000 hours (to >70% luminous output)*
**Manufacturer´s figure obtained under manufacturer´s test conditions*
Color: Black
Housing: Steel
Protection rating: IP20
Location: Indoor use only, must be fastened to surface or structure
Mounting points: Integral hanging brackets (removable), side-by side mounting locks
Orientation: Any
AC power in/thru: Neutrik PowerCon
DMX data in/out: 3-pin and 5-pin locking XLR
AC power: 100-240 V nominal, 50/60 Hz
Typical total power consumption: 148 W
Power consumption figures are typical, not maximum. Allow for +/-10% variation.
Cooling: Forced air (temperature-regulated, low noise)
Maximum ambient temperature (Ta max.): 40° C (104° F)
Minimum ambient temperature (Ta min.): 0° C (32° F)
Mounting brackets incl. screws
Power cable 1.5 m (4.9 ft.)
RUSH Software Uploader 1™

Downloads

Image not found or type unknown

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.