

## TANNOY Mercury 7.4 Light Oak

Šifra: 10808

Kategorija proizvoda: Podnostojeći Zvučnici

Proizvođač: Tannoy

**Cena: 29.880,00 rsd**



The Mercury 7.4 floorstanding loudspeaker is the big hitter of the new Mercury 7 series. Delivering unrivalled power and musical entertainment, this new Mercury flagship is bigger, more powerful and more dynamic than ever. Suitable for larger listening rooms or where high volumes are required, Mercury 7.4's 44 litre twin-ported cabinet, dual 178mm (7.00") mid/bass drivers and refined 28mm (1.1") soft dome tweeter pack a mighty punch.

To further enhance imaging and produce the widest soundstage, the drivers are positioned in a D'Appolito driver configuration. By placing the tweeter centrally between the two bass/mid drivers, the speaker's dispersion characteristics are smoothed through the critical crossover region resulting in a highly articulate musical performance on or off the loudspeaker's main axis. This eliminates the traditional 'sweet spot' to deliver peak performance across more seats in your listening room.

As befits a flagship of any Tannoy loudspeaker series, the Mercury 7.4 boasts class leading peak power handling at 300 Watts and extremely high 93dB/watt efficiency making it suitable for the broadest range of partnering equipment. Along with the high-current crossover and audiophile grade components, Mercury 7.4 can be driven hard and deliver realistic dynamics, yet remains subtle and refined at everyday listening levels. Its wideband frequency response from 32Hz up to over 32kHz ensures peak performance with standard as well as High Resolution Audio formats to make the Mercury 7 series flagship model a future-proof powerhouse.

**Drive Unit**  
Only one found or type unknown

### **Drive Unit**

To make the latest generation of Mercury even better than the award-winning Mercury Vi series required completely new driver designs. The new Mercury 7 mid/bass drivers are fitted with a significantly larger than previous models, enabling them to deliver deeper bass with greater punch than any competitor design.

Image not found or type unknown

### **Cone Material**

The Mercury 7 cone uses an updated version of Tannoy's proprietary multi-fibre cone material with a smoothly sculpted profile for better dispersion and more accurate midrange reproduction. The light and stiff cone delivers fast, tight bass while the new computer optimised rubber surround provides exceptionally high excursion without over-damping the cone.

Image not found or type unknown

### **Tweeter**

The new 28 mm (1.10") Mercury 7 tweeter uses a soft woven polyester dome that is coated to Tannoy's exacting specification with a micro layer of nitro-urethane. This special lamination process damps the dome and pushes its break-up frequencies far beyond the audio range. The treble is smooth and detailed with an extended frequency response to over 32 kHz.

Image not found or type unknown

### **Technology**

Throughout the signal path, Mercury 7 benefits from technologies trickled down from Tannoy's high-performance and luxury speaker ranges. The crossovers employ close tolerance components throughout, including low-loss laminated iron core inductors for seamless integration between drivers. Internal wiring is silver-plated Oxygen Free Copper and speaker terminals utilise Tannoy custom designed gold-plated binding posts.

### Construction

Mercury 7 cabinets are the series' most acoustically neutral enclosures to date. By creating a rigid, low resonant foundation for the drivers, has always been the starting point for Mercury models, ensuring reduced cabinet colouration giving a natural and more spacious sound.

### Cabinet Material

The new cabinets also boast extensive use of Tannoy's Differential Materials Technology (DMT) compound. Used in critical areas, such as driver to cabinet interface and crossover component mounts, this high tech material damps unwanted vibrations and further reduce colouration. As with DMT application in Tannoy's luxury and Prestige loudspeaker ranges, the treatment delivers a crisper, more opensound with enhanced detail and micro-dynamics.

### Performance

<b>Recommended amplifier power (Watts RMS)</b>	20 - 150
<b>Continuous power handling (Watts RMS)</b>	75
<b>Peak power handling (Watts)</b>	300
<b>Sensitivity (2.83 Volts @ 1m)</b>	93 dB
<b>Nominal Impedance (Ohms)</b>	8
<b>Frequency response (-6 dB)</b>	32 Hz - 32 kHz

### Drive Units

<b>Dual Concentric High frequency</b>	28 mm (1.1") N system
<b>Dual Concentric Low frequency</b>	178 mm (7") M

### Crossover

<b>Crossover Frequency</b>	2.4 kHz
----------------------------	---------

<b>Crossover Type</b>	Passive low loss
<b>Construction</b>	
<b>Enclosure type</b>	Twin rear porte
<b>Volume</b>	44.0 l (1.55 cu.
<b>Dimensions (H x W x D) (inc plinth)</b>	955 x 314.3 x 3 (37.6 x 12.4 x 1
<b>Net weight</b>	15.0 kg (33.1 lbs)