

MOTU AUDIO EXPRESS HYBRID

Šifra: 7732

Kategorija proizvoda: USB Zvučne kartice

Proizvođač: MOTU

Cena: 53.280,00 rsd

6 x 8 physical input/output channels — all channels are available simultaneously and operate independently.

8-bus digital mixer — routes and mixes all six inputs to any output pair.

Two mic/guitar combo jacks — provide hi-Z 1/4" guitar input or XLR mic input with phantom power, 20 dB pad, Precision Digital Trim™, and plenty of gain.

Stereo main outs — on balanced TRS quarter-inch jacks. Connect directly to powered speakers (or other line-level analog destination).

Stereo headphone output on quarter-inch jack with independent volume control. Precision Digital Trim™ — digitally controlled analog trim on all inputs provides adjustments in approximately 1 dB increments. Fine-tune the balance of your inputs and then save/recall trim configurations.

CueMix FX cross-platform mixing software — attractive on-screen graphic mixing with an instrument tuner and audio analysis tools including real-time FFT display, spectrogram "waterfall" display, oscilloscope, X-Y plot and linear or polar phase analysis.

Front panel volume control of main outs and headphone jack.

Time code support — directly resolves to (or generates) time code via any quarter-inch input or output, without the need for an extra synchronizer.

Sample-accurate MIDI — connect a MIDI controller and/or sound module with no separate interface needed. MIDI I/O is sample-accurate with supporting software.

DC-coupled TRS outputs — can be used with [Volta™](#) (sold separately) to manipulate and sequence voltage-controlled modular synthesizers from a host DAW. Includes native 32- and 64-bit drivers for Mac OS X and Windows 7/Vista, including ASIO, WDM, Wave, Core Audio, and Core MIDI. Supports all popular Mac and Windows audio software. [Full system requirements.](#)

Includes AudioDesk full-featured sample-accurate workstation software for the Mac with recording, editing,

MOTU AUDIO EXPRESS HYBRID

Audio Express feature summary

6-input, 6-output audio interface for Mac and Windows. Hybrid FireWire/USB 2.0 connectivity — connect to your Mac or PC via either bus-powered Firewire or hi-speed USB2.

Four separate mixes — each output pair (main outs, line outs, S/PDIF out, and phones) can have a completely different mix of all six inputs, with or without computer tracks.

Stereo analog inputs — on line-level, balanced TRS quarter-inch jacks. Great for keyboards or other line level-input signals.

Stereo 24-bit 96kHz S/PDIF digital in/out.

Support for standard sample rates up to 96 kHz.

Front-panel mixing and control — each input has its own dedicated volume knob. Control multiple mixes with clear feedback from front panel LEDs and metering.

Stand-alone operation — bring the Audio Express to your gig, with or without a computer. Just plug in the included power adapter and you are ready to go. Need to tweak the mix? Just turn the front-panel knobs.

Expandable — add additional interfaces for more I/O as your needs grow.

Direct Digital Synthesis™ (DDS) — a DSP-driven phase lock engine and internal clock source that produces imperceptibly low jitter characteristics (below the noise floor), even when the Audio Express is resolved to an external clock source via SMPTE time code.

Foot switch input — connect a standard foot pedal switch (sold separately) for hands-free punch-in and punch-out while recording. Or map the pedal to any keystroke function in your host software.

Plug-and-play operation with your Mac or PC via FireWire or USB2 — compatible with all current and recent generation Macs and PCs.

100% compatible with all host-based effects processing in today's popular audio programs.

mixing, real-time 32-bit effects processing & sample-accurate sync.

Chassis dimensions, excluding rack ears and front and back panel knobs and connectors: 9.5 × 7 × 1.75 inches (24.13 × 17.78 × 4.45 cm). Knobs and connectors extend up to 0.5 inch (1.27 cm) from front and back panels, adding 1 inch (2.54 cm) to depth. With rack ears attached, fits one half of a standard 19 inch (48.26 cm) rack at 1U high.

Bus-powered FireWire operation; no need for external power when operating as a FireWire interface connected to a computer. A power supply is included for stand-alone operation.