1090e not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

MOTU AUDIO EXPRESS HYBRID

MOTU AUDIO EXPRESS HYBRID

Šifra: 7732

Kategorija prozivoda: USB Zvučne kartice

Proizvođač: MOTU

Cena: **53.280,00** rsd

Audio Express feature summary

6-input, 6-output audio interface for Mac and Windows.

6 x 8 physical input/output channels — all channels are available simultaneously and operate independently. 8-bus digital mixer — routes and mixes all six inputs to any output pair.

Two mic/guitar combo jacks — provide hi-Z 1/4" guitar input or XLR mic input with phantom power, 20 dB pad, Precision Digital Trim™, and plenty of gain.

Stereo main outs — on balanced TRS quarter-inch jacks. Connect directly to powered speakers (or other line-level analog destination).

Stereo headphone output on quarter-inch jack with independent volume control.

Precision Digital Trim[™] — digitally controlled analog trim on all inputs provides adjustments in approximately 1 dB increments. Fine-tune the balance of your inputs and then save/recall trim configurations.

CueMix FX cross-platform mixing software — attractive on-screen graphic mixing with an instrument tuner and audio analysis tools including real-time FFT display, spectrogram "waterfall" display, oscilloscope, X-Y plot and linear or polar phase analysis.

Front panel volume control of main outs and headphone jack.

Time code support — directly resolves to (or generates) time code via any quarter-inch input or output, without the need for an extra synchronizer.

Sample-accurate MIDI — connect a MIDI controller and/or sound module with no separate interface needed. MIDI I/O is sample-accurate with supporting software.

DC-coupled TRS outputs — can be used with $Volta^{TM}$ (sold separately) to manipulate and sequence voltage-controlled modular synthesizers from a host DAW.

Includes native 32- and 64-bit drivers for Mac OS X and Windows 7/Vista, including ASIO, WDM, Wave, Core Audio, and Core MIDI. Supports all popular Mac and Windows audio software. Full system requirements.

Hybri Mac o USB2 outs, differ

Stere

Supp

quart

level-

Front own o with o

Stand your (include to two

Expai your

Direc

lock e imper floor) switch punct keyst

Plug-FireW recer

100%

in today's popular audio programs.

Includes AudioDesk full-featured sample-accurate workstation software for the Mac with recording, editing, mixing, real-time 32-bit effects processing & sample-accurate sync.

Chassis dimensions, excluding rack ears and front and back panel knobs and connectors: $9.5 \times 7 \times 1.75$ inches ($24.13 \times 17.78 \times 4.45$ cm). Knobs and connectors extend up to 0.5 inch (1.27 cm) from front and back panels, adding 1 inch (2.54 cm) to depth. With rack ears attached, fits one half of a standard 19 inch (48.26 cm) rack at 1U high.

Bus-p powe conne for st