

MARTIN WISMAN MXR 800

Šifra: 12049

Kategorija proizvoda: PA Predpojačala

Proizvođač: Martin Wisman



Cena: 27.480,00 rsd

Standard machine cabinet type 1 U height design, black aluminum oxide drawbench panel. With 8 inputs interface which can be converted independently, adopting European style terminals.

Double bus design with main channel/ accessory channel output selector.

One independent accessory input interface, adopting European style terminals.

Multi-channel input audio mixed into public output bus directly, adopting balanced input and output.

With line and mic selective switch for each channel, output to AUX connector.

Each input channel can be gain controlled, input with low cut filter.

Knob input level can be controlled independently in each channel.

With phantom power switch power supplied to condenser microphone.

Knob is independently controlled in main output and auxiliary output.

Main output is equipped with voltage limit which is with by-pass switch, threshold value and ratio value and can be controlled.

With LED output indicator on panel, and with earphone output function.

1-8MIC/ Line - 0.25mV/5K Ω balanced, \pm 7.75V/5K Ω balanced

AUX1 RCA In - \pm 0.775V/20K Ω unbalanced

Output Level/Impedance

Master 1, -2 - +4 dB μ /440 Ω balance (MAX: \pm 7.75V)

Main Output MIC Pad - -50 dB

Low Cut - 18 dB/octave at 100 Hz

Frequency Response

Less Than - -1dB(20Hz~20KHz)

S/N Ratio

MIC - More than 60dB

Line - More than 75dB

THD

MIC - Less than 0.05%

Line - More than 0.03%

Cross-talk

MIC - More than 60dB

Line - More than 75dB

LIMITER/COMPRESSOR

Threshold Adj. Range - -20 dB to +20 dB

Ratio Adj. Range - 0 to 100%

LED Bar Graph - -18, -12, -6, -3, 0, +3, +6, +12VU (0 VU = +4 dB) Average or Peak reading

Power Consumption

Power - 20W

Power Supply - ~110V/60Hz or ~230V/50Hz

Dimensions - 484x190x44mm

Weight - 3.9Kg